

## NAME

ctxtools – clean up temporary ConTeXt files, install latest ConTeXt

## SYNOPSIS

**ctxtools** [ *OPTION* ... ]

## DESCRIPTION

**ctxtools** is useful for dealing with ConTeXt source and generated files and for installing new versions of ConTeXt.

## OPTIONS

**--help** Print the available options.

### **--purgefiles**

Get rid of many temporary files generated by ConTeXt. You can give the **--all** option to remove a larger fraction of those files, and the **--recurse** option to remove these files also in subdirectories.

### **--contextversion**

Show the date of the ConTeXt macros and the format file. Useful after upgrading ConTeXt (perhaps using **--updatecontext**) to check whether the new formats and macros are visible to the TeX path searches (see **kpsewhich**(1)).

### **--updatecontext**

Download the latest ConTeXt distribution and install it in the TEXMFLOCAL tree (see **kpsewhich**(1) for information on TeX path searching). TEXMFLOCAL usually points to a system-wide location. If you want to install the new ConTeXt in your home directory (i.e. an install for one user), then set the TEXMFLOCAL environment variable while running **ctxtools**. For example, using the syntax of the Bourne shell **sh**(1):

```
TEXMFLOCAL=$HOME/texmf ctxtools --updatecontext
```

### **--documentation**

Generate a *.ted* file from the source file. See also the **--module** option to **texexec**(1).

### **--patternfiles** [languagecode]

Generate pattern files. You can also give the **--all**, **--xml**, and **--utf8** options.

## ENVIRONMENT

TEXMFLOCAL

Used by **--updatecontext** to decide where to install the distribution.

## SEE ALSO

**texexec**(1), **texmfstart**(1).

[ConTeXt wiki](http://www.contextgarden.net) <<http://www.contextgarden.net>>.

## BUGS

This manual page is not complete.

**AUTHOR**

This manual page was written by Sanjoy Mahajan <sanjoy@mit.edu>. It is in the public domain.