

NAME

`vptovf` – convert virtual property lists to virtual font metrics

SYNOPSIS

vptovf [**-verbose**] *vpl_name*[**.vpl**] [*vfm_name*[**.vf**] [*tfm_name*[**.tfm**]]]

DESCRIPTION

This manual page is not meant to be exhaustive. The complete documentation for this version of T_EX can be found in the info file or manual *Web2C: A TeX implementation*.

The **vptovf** program translates a (human-oriented) property list file to a pair of (program-oriented) files in the VF (virtual font) and TFM (T_EX font metric) formats. Thus, a virtual font file can be edited and its exact contents can be displayed mnemonically. New virtual fonts, which map characters as seen by T_EX into an arbitrary sequence of low-level typesetting operations, can also be created in this way.

All three filenames, *vpl_name*, *vf_name*, and *tfm_name*, are extended with the appropriate suffix, if they lack one.

OPTIONS

Without the **-verbose** option, **vptovf** operates silently. With it, a banner and progress report are printed on *stdout*.

SEE ALSO

pltotf(1), **tftopl**(1), **vftovp**(1).

AUTHORS

Donald E. Knuth wrote the program, based in part on an idea of David Fuchs, starting with the code for **pltotf**(1). Karl Berry adapted it for compilation with **web2c**.