

The `komacv` class*

Salome Södergran
`salome.soedergran@gmx.ch`

April 12, 2017

Abstract

The `komacv` class makes typesetting an attractive CV easy. While it comes with several predefined styles it is still highly customizable. Virtually all settings can be controlled by user commands.

Contents

1	Introduction	2
2	Engines	3
3	In the preamble	3
3.1	Documentclass options	3
3.2	Personal data (header and footer)	3
3.3	Symbols	4
3.4	Picture	5
3.5	Lengths	5
3.6	Colors	6
3.7	Encoding and Fonts	7
3.8	Page number	7
3.9	Hypersetup	7
4	In the document	8
4.1	<code>\maketitle</code>	8
4.2	Sections and subsections	8
4.3	<code>\cvitem</code>	8
4.4	<code>\cvdoubleitem</code>	9
4.5	<code>\cvlistitem</code> and <code>\cvlistdoubleitem</code>	9
4.6	<code>\cventry</code>	9
4.7	<code>\cvitemwithcomment</code>	9
4.8	Links	9
4.9	Itemize	10

*This document corresponds to `komacv` v1.1, dated 2017/04/12.

5	Styles	10
5.1	The classic style	10
5.2	The casual style	10
5.3	The oldstyle style	10
6	Examples	10
7	Bugs and things to do	10
8	New CV styles	11
9	Acknowledgements	11
10	Implementation	11
10.1	The komacv class	11
10.2	The classic style	25
10.3	The casual style	28
10.4	The oldstyle style	30

1 Introduction

This class originates from an imitation of the `moderncv` class. Thanks to Xavier Danaux for that fine class! While `komacv` owes a lot to the original code, it does not pretend to be a precise copy and does not intend to keep up with the further development of the `moderncv` class. The original class was taken as an important starting point but it is likely that the further development will take different directions.

While `moderncv` is a stand-alone class, this one is a wrapper class building upon the KOMA-class `scrartcl` (hence the `koma-` in the name of this class). This gives users more flexibility as the page layout is easily adjustable and incompatibilities with other packages are less likely to occur. The incompatibility of the `moderncv` class with the `biblatex` package was actually the main reason for my building the predecessor of this class, the `koma-moderncvclassic` package. Compared with that package, this class offers much more flexibility and customizability, comes with a variety of styles and is extensible (new styles can be added easily).

With `\documentclass{komacv}` at the beginning of your document the commands and environments of both this class and the `scrartcl` class become available.

The variants of the file `komacv_example` which come with this package show exemplarily how a document with `komacv` might be structured and how the typical commands are to be used. They are not intended as examples of good style but as demonstrations of the potential of the `komacv` class. In this documentation all commands and features are explained.

Please note that `komacv` does not (yet?) provide for the possibility of typesetting the covering letter as well.

2 Engines

This class can be run with either $X_{\text{T}}\text{E}_{\text{X}}$, $X_{\text{L}}\text{A}_{\text{T}}\text{E}_{\text{X}}$, $\text{LuaT}_{\text{E}}\text{X}$, $\text{LuaL}_{\text{A}}\text{T}_{\text{E}}\text{X}$ or $\text{pdfL}_{\text{A}}\text{T}_{\text{E}}\text{X}$. See also 3.7.

3 In the preamble

3.1 Documentclass options

`komacv` accepts the following key-value pairs as optional arguments of `\documentclass`:

`[xcolor=<value>]`

The value of the key `xcolor` is passed to the `xcolor` package and takes the name of the color spectrum. These are the names of color spectra defined by `xcolor`: `svgnames`, `dvipsnames`, `x11names`. If the option is not set or the key `xcolor` is given without a value, then the default is used which is `x11names`.

`[color=<value>]`

The value of the key `color` is the name of the color to be used in special elements of the document like section and subsection headers of the document (depending on the chosen style). The name is either a base color name (black, blue, green a.s.o.) or a color name according to the chosen color spectra defined by `xcolor` (e.g. `Firebrick2` in `x11names`). See the `xcolor` documentation for a list of valid color names. Color definitions such as `red!75` or `blue!30!green` are also accepted. Yet another possibility is to specify `mycolor` in the preamble (see below). If the `color` option is given without an argument or not given at all,

`[color=mycolor]`

is assumed as default.

If `mycolor` was not defined, the fallback is `blue` instead of `mycolor`.

`[style=<value>]`

This option loads the style variant. The default is `style=classic`. Other variants currently available are: `casual` and `oldstyle`. Other variants may follow in time, contributions are very welcome! See the example documents to see the different layouts the styles produce.

`\KOMAOptions`

In addition to these `komacv` specific options, all KOMA-options may be used as with the KOMA-classes. They may be given either in the option list of `\documentclass` or with the help of `\KOMAOptions` somewhere in the preamble:

`\documentclass[<key=value>]{komacv}` or

`\KOMAOptions{<key1=value1,key2=value2>}`

and will be passed to the `scartcl` class (on which the `komacv` class is built).

3.2 Personal data (header and footer)

To specify your personal data set the macros with `\renewcommand`:

`\renewcommand*{<command>}{<Definition>}`, for example:

`\renewcommand*{title}{Curriculum vitae}`.

`\headline`

With `\headline` you can set – guess what? – a headline for the whole document, either a title (like “Curriculum vitae”) or your name, which may come in handy if you have a very long name that is otherwise being displayed

3.4 Picture

<code>\photo</code>	To include a picture into the head of your CV set <code>\photo[<i>frame</i>]{<i>width</i>}{<i>path/pic</i>}</code> in the preamble.
<code>[frame]</code>	With <code>frame</code> as optional argument the picture is set into a frame, by default in the color chosen as document color. See below (3.5, 3.6) how to change the color and the thickness of the frame.
<code>[mframe]</code>	With the <code>classic</code> style, <code>[mframe]</code> (for margin frame) will extend the picture into the right page margin with half its width (or according to the length of <code>\mframepicshift</code> , if defined). With other styles <code>[mframe]</code> is an alias for <code>[frame]</code> .
<code><width></code>	The first mandatory argument takes the width the picture is resized to, all common L ^A T _E X measures may be used.
<code><path/pic></code>	The second mandatory argument takes the name of the picture file. If the picture is not located in the same directory as the document and no <code>\graphicspath</code> was defined, the path to the picture file must be given as well. This argument will be passed to the <code>graphicx</code> package, so all file types that <code>graphicx</code> can handle are allowed (jpg/jpeg, png, pdf).

3.5 Lengths

The following lengths may be changed with the usual L^AT_EX commands `\setlength`, `\addtolength` and `\settowidth`.

<code>\hintscolwidth</code>	The width of the hint column. The default value is <code>0.2\textwidth</code> .
<code>\sepcolwidth</code>	The distance between the hint column and the main column. In <code>\cvdoubleitem</code> and <code>\cvlistdoubleitem</code> this is also the distance between the aligned items, or the aligned pairs of header and item.
<code>\infocolwidth</code>	In <code>oldstyle</code> style the address and possible extra information are presented in the left margin of the width <code>\infocolwidth</code> . Its default value is <code>3.5cm</code> .
<code>\sepinfocolwidth</code>	In <code>oldstyle</code> style the distance between the info column and the main column.
<code>\maincolwidth</code>	The width of the main column in all elements, except for the <code>doubleitem</code> elements.
<code>\dbitemmaincolwidth</code>	Width of each maincolumn where two items are set per line with <code>\cvdoubleitem</code> .
<code>\listitemsymbolwidth</code>	Horizontal space reserved for the symbol in <code>\listitem</code> entries. By default this is the width of <code>\listitemsymbol</code> followed by a nonbreaking space (<code>~</code>).
<code>\listitemmaincolwidth</code>	Width of the maincolumn where <code>\cvlistitem</code> is in use. By default this is the <code>\maincolumnwidth</code> minus <code>\listitemsymbolwidth</code> .
<code>\listdbitemmaincolwidth</code>	Width of each maincolumn where two items are set per line with <code>\cvlistdoubleitem</code> .
<code>\titlesepwidth</code>	Horizontal space between the text information given in the header and the picture (if <code>\photo</code> is set).
<code>\mframepicshift</code>	If a picture is set with the optional argument <code>[mframe]</code> of <code>\photo</code> the picture will be placed partly in the margin. The length <code>\mframepicshift</code> controls how much the picture will be moved to the right (from the right text margin). This works only with the <code>classic</code> style; with other styles <code>\mframepicshift</code> does nothing.

<code>\fboxrule</code>	The thickness of the frame around your picture and the space between the frame and the picture (if <code>\photo</code> is set with either <code>[frame]</code> or <code>[mframe]</code> as optional argument).
<code>\fboxsep</code>	
<code>\quotewidth</code>	The width of the quote.
<code>\footerwidth</code>	The width of the footer (used in <code>casual</code> style).
<code>\aftertitlevspace</code>	Vertical space between head and quote (or main text, if no quote is given).
<code>\afterquotevspace</code>	Vertical space between quote and main text. Used only if quote is given.
<code>\afterelementsvspace</code>	Vertical space inserted after each element (<code>\cvitem</code> , <code>\cventry</code> , ...).
<code>\beforesecvspace</code>	Vertical space inserted before or after sections and subsections. Use an elastic length (e.g. something like <code>3ex plus .2ex minus .1ex</code> or <code>\baselineskip</code>). Note that the section and subsection definition of <code>komacv</code> needs improvement, so the setting of these lengths may not produce the desired result and the result may change in future versions.
<code>\aftersecvspace</code>	
<code>\beforesubsecvspace</code>	
<code>\aftersubsecvspace</code>	

3.6 Colors

<code>\colorlet</code>	The color theme of the whole document is changed via the documentclass options as described above (3.1). If you want to change the color of certain elements only you may do so with the command <code>\colorlet{<elementcolorname>}{<color>}</code> , for example <code>\colorlet{firstnamecolor}{red}</code> (basic color name) or <code>\colorlet{firstnamecolor}{Firebrick2}</code> (color name as defined in the color spectrum specified with the documentclass option [<code><xcolor= ></code>], <code>xllnames</code> in this case) or <code>\colorlet{sectitlecolor}{firstnamecolor}</code> (make the sectiontitles have the same color as the firstname).
<code>firstnamecolor</code>	
<code>familynamecolor</code>	With the colornames given beside you can change the color of the corresponding elements that are used in the head (or foot) of your CV. By default (i.e. if you do not change the colors with <code>\colorlet</code>) the text in the CV head is black. More precisely, the <code>firstnamecolor</code> is black, the other elements of the head take the color of the first name. So if you want to change the color of the whole text in the head, it suffices to change <code>firstnamecolor</code> . If you want the different elements to have different colors, you have to define them separately.
<code>acadtitlecolor</code>	
<code>addresscolor</code>	
<code>quotecolor</code>	
<code>framecolor</code>	<code>framecolor</code> and <code>framebackcolor</code> may be specified when <code>\photo</code> is used with either <code>[frame]</code> or <code>[mframe]</code> as optional argument. <code>framecolor</code> sets the color of the frame around the picture, <code>framebackcolor</code> of the interspace between frame and picture. By default <code>framecolor</code> is the color of the document colortheme, <code>framebackcolor</code> is white.
<code>framebackcolor</code>	
<code>secbarcolor</code>	By default the section headers, the bar beside the section headers (if provided by the current style) and the subsection headers are given in the color of the document colortheme. To change the settings use the colornames given beside.
<code>seccolor</code>	
<code>subseccolor</code>	
<code>hintcolor</code>	<code>hintcolor</code> is the name of the color used for the text in the hint column. By default it is black.
<code>\definecolor</code>	If you want to assign a color to a name you can do so with the <code>\definecolor</code> command from the <code>xcolor</code> :
<code>mycolor</code>	<code>\definecolor{mycolor}{cmyk}{0.92,0,0.87,0.09}</code> .

This new (or any other) name may be given as value to the `color` key in the documentclass optionlist and used with `\colorlet` as just described.

3.7 Encoding and Fonts

This class does not load any fonts. The different engines have their own ways of handling fonts and it is up to the user to choose the engine and a font suitable for the style in use. With X_YTeX, X_YL^ATeX, LuaTeX and Lua^ATeX `fontspec` is loaded by `komacv`, with pdfL^ATeX `utf8` is loaded as input encoding and `T1` as fontencoding. Set the desired font in a usual engine-specific way, e. g. with `\setmainfont{font}` for X_YTeX, LuaTeX and friends and with `\usepackage{font}` for pdfL^ATeX.

The element specific font attributes are set with `\newkomafont` and may be adjusted with `\setkomafont` or `\addtokomafont`.

For example:

```

firstnamefont      \setkomafont{firstnamefont}{\fontsize{24}{26}\itshape} or
familynamefont    \addtokomafont{familynamefont}{\scshape} or
acadtitlefont     \setkomafont{addressfont}{\usekomafont{quotefont}}.
addressfont
quotefont
hintfont
commentfont
commentmainfont

linkfont
httplinkfont
emailinkfont

section
subsection

```

By default `familynamefont` is the same as `firstnamefont`, so if you want to change both it suffices to change `firstnamefont`. `addressfont` is used for the whole addressblock, including address, phone and fax numbers, email address, homepage address and extrainfo.

`commentfont` and `commentmainfont` are used in `\cvitemwithcomment` only.

`linkfont`, `httplinkfont`, `emailinkfont` are used for the link commands `\link`, `\httplink` and `\emailink` (described below 4.8).

Font attributes of elements that belong to the `scartcl` class are also changed in the usual KOMA-way, e. g.:

```

\setkomafont{section}{\Large\sffamily\mdseries\slshape}.
\addtokomafont{subsection}{\bfseries}.

```

Switching to a sans-serif font as default is done in the usual L^ATeX way:

```

\renewcommand*{\familydefault}{\sfdefault}.

```

3.8 Page number

`\totalpagemark`

The command `\totalpagemark` prints the total number of pages. With the following definition in your preamble you will get the page number followed by a slash and the total number of pages in the outer foot of your pages (with the help of `sclayer-scrpage` which is loaded by the documentclass):

```

\pagestyle{scrheadings}
\clearscrheadfoot
\ofoot{\pagemark/\totalpagemark}

```

3.9 Hypersetup

`\hypersetup`

To change the way hyperlinks are highlighted in the pdf document, use the `\hypersetup` command. This command is provided by the `hyperref` package which is loaded by the `komacv` class. See the `hyperref` manual for the options available.

Note: The following `\hypersetup` option keys (and these only) must *not*

```

pdfauthor
pdftitle
pdfsubject
pdfkeywords

```

allbordercolors
citebordercolor
filebordercolor
linkbordercolor
menubordercolor
urlbordercolor
runbordercolor

urlcolor

be redefined with `\hypersetup` but with `\renewcommand`:
`pdfauthor`, `pdftitle`, `pdfsubject`, `pdfkeywords` and all `...bordercolor`
options. *For example*, do not use:

```
\hypersetup{pdftitle = {My~CV}} but rather:  
\renewcommand*\pdftitle{My~CV}.
```

This is necessary because the defaults defined by the documentclass are loaded at the end of the preamble and would overwrite any user settings.

All `\hypersetup` color options accept the same color names as does the documentclass `color` option (i. e. it depends on the setting of the documentclass option `xcolor` which names will be recognized). So you can change the color options like this:

```
\renewcommand*\urlbordercolor{green} (for the ...bordercolor op-  
tions), but  
\hypersetup{urlcolor=pink} (for all other ...color options).
```

4 In the document

4.1 `\maketitle`

`\maketitle`

With `\maketitle` at the beginning of your document your personal data and your picture as specified in the preamble will be set in the header (and possibly footer) of the first page according to the chosen style.

If you want the footer to appear on all pages, use `\pagestyle{footer}` or `\pagestyle{mypagestyle}` somewhere at the beginning of your document (not in the preamble).

4.2 Sections and subsections

To structure your CV into sections like “Education”, “Job training”, “Interests” a.s.o. use the `\section` and `\subsection` commands. They are formatted according to the current style and include no section numbering. See above (3.6 and 3.7) how to change the color and the font attributes of sections and subsections.

4.3 `\cvitem`

`\cvitem`

`\cvitem[spacing]{header}{text}` is for single pairs of header and text. The header will appear in the hint column, the main text in the main column.

The optional argument defines the vertical space after this `\cvitem` element. This applies analogously to all the elements with an optional spacing argument.

To change the vertical space used after *all* `\cv...` elements that have an optional spacing argument, change `\afterelements vspace` as described above (3.5). If the optional spacing argument is used it overrides the value of `\afterelements vspace` for the current element.

Caveat: No newlines (`\`) or paragraphs (`\par` oder empty lines) are allowed inside `\cvitem` and the other predefined elements. They will lead to an error message like:

```
! Paragraph ended before \cvitem was complete.
```

and the parsing process will stop.

4.4 `\cvdoubleitem`

`\cvdoubleitem` `\cvdoubleitem[<spacing>]{<header1>}{<text1>}{<header2>}{<text2>}` puts two pairs of header and text in one line. The first header appears in the hint column.

4.5 `\cvlistitem` and `\cvlistdoubleitem`

`\cvlistitem[<label>]{<item>}` and `\cvlistdoubleitem[<label>]{<item1>}{<item2>}` put one or two pair(s) of label and item in the main column. The hint column is left empty. If the optional argument is omitted, the label is the default label provided by the style in use or the label defined with `\listitemsymbol`.

4.6 `\cventry`

`\cventry` With the command `\cventry[<spacing>]{<years>}{<degree/job title>}{<institution/employer>}{<localization>}{<grade/...>}{<comment/job description>}` you get a more structured description. The first mandatory argument will usually be placed in the hint column (depending on the style in use), all others in the main column, each with its own formatting. Just leave empty those arguments you do not need (use empty braces `{}`). Note, however, that the second mandatory argument should not be empty (otherwise the entry in the main column will start with a comma).

4.7 `\cvitemwithcomment`

`\cvitemwithcomment` With `\cvitemwithcomment[<spacing>]{<header>}{<text>}{<comment>}` you can list a pair of header and description with a additional right-aligned comment.

4.8 Links

There are three link commands predefined:

`\link` `\link[<optional text>]{<link>}`,
`\httplink` `\httplink[<optional text>]{<link>}`, and
`\emailink` `\emailink[<optional text>]{<link>}`.

All of them take a description as optional argument and the link address as mandatory argument. The optional argument will be shown in the text, the hyperlink points to the address given in the mandatory argument. If no optional argument is given the address in the mandatory argument will be printed. The mandatory argument of `\httplink` will be prefixed with `http://`, of `\emailink` with `mailto:`. To change the font attributes of the links, see above 3.7.

`compactitem`
`compactenum`
`compactdesc`

4.9 Itemize

These are three compact versions of the standard lists `itemize`, `enumerate` and `description` (by the `enumitem` package). In the default setting within `komacv` they come without indentation or extra spacing so they fit nicely into other elements such as `\cvitem`. They are used in the usual way:

```
\begin{compactitem}
  \item text
\end{compactitem}.
```

If you use them inside other elements make sure there are no empty lines surrounding them, otherwise you will get an error message (see 4.3).

5 Styles

5.1 The classic style

In `classic` style all personal data appear in the header with the optional picture on the right side. Section and subsection headers are given in the document color and placed in the main column. On the left side of the section headers is a horizontal bar in the hint column.

5.2 The casual style

The `casual` style is built upon the `classic` style with a few changes. The main difference to the `classic` style is that the picture is set at the left of the header and the address block is set in the foot of the page. By default the foot is set on the first page only. If you want it on all pages, put `\pagestyle{footer}` at the beginning of your document.

5.3 The oldstyle style

This style provides a CV with the addressblock in the left margin and the hint column to the right. The section headers are kept simple, without section bars. To allow for three columns the `DIV` value is increased.

6 Examples

For examples see the example files `komacv.example_{style}.pdf` that come with this class. They should be located in the `doc`-directory of the tree where the class is stored. The example file `komacv_example.tex` can be used to test the various possibilities `komacv` offers. Just remove (or add) comment signs and change the preset values.

7 Bugs and things to do

Further testing and use will certainly make some bugs crawl out from the dark in which they hide from me until now. If you encounter bugs, errors or typos, or if you have suggestions how to improve the

`komacv` class and the style files, please do not hesitate to contact me at `salome.soedergran@gmx.ch`. I am thankful for any suggestions that help improving `komacv` though I dare not promise to be always very speedy in publishing a new version.

8 New CV styles

The flexibility of `komacv` makes it fairly easy to create new CV styles. If you have created a CV style of your own and want to share it with others you have two possibilities:

You can publish it on CTAN. Just make sure it will be installed in the `styles`-subdirectory of the `komacv`-directory (usually `tex/latex/komacv/styles`).

Or you can send it to me at `salome.soedergran@gmx.ch` and I will include it in the next version of `komacv`.

9 Acknowledgements

Many thanks to Ulrike Fischer, Alexander Krnzlein, Matthias C. Schmidt, Damian Martinez Dreyer, and Sebastian Rder for their suggestions and help. I am also grateful to Andreas Biemann, Simon Dreher, Paul Menzel and Dominik Waenhoven who helped to improve the now obsolete `koma-moderncvclassic.sty`.

10 Implementation

Note: The code of the styles is not part of the file `komacv.cls` but is to be found in the style files `komacv-(stylename).sty`, e.g. `komacv-classic.sty`.

10.1 The `komacv` class

Initialization

```
1   \providecommand*\mycolor{blue}
2   \RequirePackage{ifthen,kvoptions,calc}
```

Declare Options

```
3   \SetupKeyvalOptions{%
4     family=komacv,%
5     prefix=komacv@,%
6     setkeys=\kvsetkeys%
7   }
8   \DeclareStringOption[mycolor]{color}[mycolor]
9   \DeclareStringOption[x11names]{xcolor}[x11names]
10  \DeclareStringOption[classic]{style}[classic]
11  \DeclareOption*{\PassOptionsToClass{\CurrentOption}{scrartcl}}
```

Process Options

```
12  \ProcessKeyvalOptions{komacv} % evaluate keyval options
```

```

13     \ProcessOptions\relax % execute given options
Load class
14     \LoadClass[a4paper,headings=normal,fontsize=11pt,headinclude,footinclude]{scrartcl}
Packages
15     \RequirePackage[\komacv@xcolor]{xcolor}
16     \RequirePackage{%
17         etoolbox,%
18         ifpdf,%
19         ifluatex,%
20         ifxetex,%
21         scrlayer-scrpage,%
22         marvosym,%
23         array,%
24         graphicx,%
25         microtype,%
26         enumitem,
27         hyperref%
28     }
29     \RequirePackage[raggedrightboxes]{ragged2e}
Colors
30     \definecolor{myblue}{rgb}{0.2,0.3,0.65}
31     \colorlet{mycolor}{myblue}
32     \AtEndPreamble{%
33         \renewcommand*{\mycolor}{\komacv@color}
34         \colorlet{colortheme}{\mycolor}% specified in documentclass option
35         \@ifundefinedcolor{headlinecolor}{%
36             \colorlet{@headlinecolor}{black}}{%
37             \colorlet{@headlinecolor}{headlinecolor}}
38         \@ifundefinedcolor{firstnamecolor}{%
39             \colorlet{@firstnamecolor}{black}}{%
40             \colorlet{@firstnamecolor}{firstnamecolor}}
41         \@ifundefinedcolor{familynamecolor}{%
42             \colorlet{@familynamecolor}{@firstnamecolor}}{%
43             \colorlet{@familynamecolor}{familynamecolor}}
44         \@ifundefinedcolor{acadtitlecolor}{%
45             \colorlet{@acadtitlecolor}{@firstnamecolor}}{%
46             \colorlet{@acadtitlecolor}{acadtitlecolor}}
47         \@ifundefinedcolor{addresscolor}{%
48             \colorlet{@addresscolor}{@firstnamecolor}}{%
49             \colorlet{@addresscolor}{addresscolor}}
50         \@ifundefinedcolor{quotecolor}{%
51             \colorlet{@quotecolor}{@firstnamecolor}}{%
52             \colorlet{@quotecolor}{quotecolor}}
53         \@ifundefinedcolor{secbarcolor}{%
54             \colorlet{@secbarcolor}{colortheme}}{%
55             \colorlet{@secbarcolor}{secbarcolor}}
56         \@ifundefinedcolor{seccolor}{%

```

```

57     \colorlet{@seccolor}{colortheme}}{%
58     \colorlet{@seccolor}{seccolor}}
59 \@ifundefinedcolor{subseccolor}{%
60     \colorlet{@subseccolor}{colortheme}}{%
61     \colorlet{@subseccolor}{subseccolor}}
62 \@ifundefinedcolor{hintcolor}{%
63     \colorlet{@hintcolor}{black}}{%
64     \colorlet{@hintcolor}{hintcolor}}
65 \@ifundefinedcolor{framecolor}{%
66     \colorlet{@framecolor}{colortheme}}{%
67     \colorlet{@framecolor}{framecolor}}
68 \@ifundefinedcolor{framebackcolor}{%
69     \colorlet{@framebackcolor}{white}}{%
70     \colorlet{@framebackcolor}{framebackcolor}}
71 } % end AtEndPreamble

```

Encoding and Fonts

```

72 \ifboolexpr{bool{xetex} or bool{luatex}}{%
73     \RequirePackage{fontspec}%
74 }{%
75     \RequirePackage[utf8]{inputenc}
76     \RequirePackage[T1]{fontenc}%
77 }
78 \newkomafont{headlinefont}{\fontsize{30}{32}\mdseries\upshape}
79 \newkomafont{firstnamefont}{\Huge\mdseries\upshape}
80 \newkomafont{familynamefont}{\usefonttokomafont{firstnamefont}}
81 \newkomafont{acadtitlefont}{\LARGE\mdseries\itshape}
82 \newkomafont{addressfont}{\normalsize\mdseries\itshape}
83 \newkomafont{quotefont}{\large\itshape}
84 \newkomafont{hintfont}{\}
85 \newkomafont{linkfont}{\}
86 \newkomafont{httplinkfont}{\}
87 \newkomafont{emallinkfont}{\}
88 \newkomafont{commentmainfont}{\bfseries} % in \cvitemwithcomment
89 \newkomafont{commentfont}{\footnotesize\itshape} % in \cvitemwithcomment
90 \setkomafont{section}{\Large\sffamily\mdseries\upshape}
91 \setkomafont{subsection}{\large\sffamily\mdseries\upshape}

```

Lengths

```

92 \setlength\parindent{0pt}
93 \setlength\columnsep{10\p@}
94 \setlength\columnseprule{0\p@}
95 \newlength\@komacvtextwidth
96 \newlength\@hintscolwidth
97 \newlength\hintscolwidth
98 \setlength\hintscolwidth{0pt}
99 \newlength\@sepcolwidth
100 \newlength\sepcolwidth
101 \setlength\sepcolwidth{0pt}
102 \newlength\@maincolwidth

```

```

103 \newlength\maincolwidth
104 \setlength\maincolwidth{Opt}
105 \newlength\quotewidth
106 \newlength\quotewidth
107 \setlength\quotewidth{Opt}
108 \newlength\@dbitemmaincolwidth
109 \newlength\dbitemmaincolwidth
110 \setlength\dbitemmaincolwidth{Opt}
111 \newlength\@listitemsymbolwidth
112 \newlength\listitemsymbolwidth
113 \setlength\listitemsymbolwidth{Opt}
114 \newlength\@listitemmaincolwidth
115 \newlength\listitemmaincolwidth
116 \setlength\listitemmaincolwidth{Opt}
117 \newlength\@listdbitemmaincolwidth
118 \newlength\listdbitemmaincolwidth
119 \setlength\listdbitemmaincolwidth{Opt}
120 \newlength\@titlepicwidth
121 \newlength\@titlesepwidth
122 \setlength\@titlesepwidth{Opt}
123 \newlength\titlesepwidth
124 \setlength\titlesepwidth{Opt}
125 \newlength\@mframepicshift
126 \newlength\mframepicshift
127 \setlength\mframepicshift{Opt}
128 \newlength\@commentmainlength
129 \newlength\@commentlength
130 \newlength\@titlenamewidth
131 \newlength\@titlenamemaxwidth
132 \newlength\titlenamemaxwidth
133 \setlength\titlenamemaxwidth{Opt}
134 \newlength\@titlenamefullwidth
135 \newlength\@titledetailwidth
136 \newlength\@infocolwidth
137 \newlength\infocolwidth
138 \setlength\infocolwidth{Opt}
139 \newlength\@sepinfocolwidth
140 \newlength\sepinfocolwidth
141 \setlength\sepinfocolwidth{Opt}
142 \newlength\komacvinfocolextrawidth % witout @ for use inside document (addmargin)
143 \newlength\@footerwidth
144 \setlength\@footerwidth{.6\textwidth}
145 \newlength\@fboxwidth
146 \newlength\footerwidth
147 \setlength\footerwidth{Opt}
148 \newlength\@aftertitlevspace
149 \newlength\aftertitlevspace
150 \setlength\aftertitlevspace{Opt}
151 \newlength\@afterquotevspace
152 \newlength\afterquotevspace

```

```

153 \setlength\afterquotevspace{0pt}
154 \newlength\@afterelementsospace
155 \newlength\@afterelementsospace
156 \newlength\@beforeseccospace
157 \newlength\beforeseccospace
158 \setlength\beforeseccospace{0pt}
159 \newlength\@afterseccospace
160 \newlength\afterseccospace
161 \setlength\afterseccospace{0pt}
162 \newlength\@beforesubseccospace
163 \newlength\beforesubseccospace
164 \setlength\beforesubseccospace{0pt}
165 \newlength\@aftersubseccospace
166 \newlength\aftersubseccospace
167 \setlength\aftersubseccospace{0pt}
168
169 \AtEndPreamble{%
170 % infocol (oldstyle)
171 \setlength{\@infocolwidth}{\infocolwidth}
172 \setlength{\@sepinfocolwidth}{\sepinfocolwidth}
173 \setlength\komacvinfocolwidth{\@infocolwidth+\@sepinfocolwidth}
174 \setlength\komacvtextwidth{\textwidth-\komacvinfocolwidth}
175
176 % fboxextra (picture frame)
177 \newlength\@fboxextra
178 \setlength\@fboxextra{\fboxsep+\fboxrule}
179
180 % hintscolumn
181 \ifdimequal{\hintscolwidth}{0pt}{%
182 \setlength\@hintscolwidth{.2\komacvtextwidth}
183 }{%
184 \setlength{\@hintscolwidth}{\hintscolwidth}%
185 }
186
187 % separatorcolumn
188 \ifdimequal{\sepcolwidth}{0pt}{%
189 \setlength\@sepcolwidth{2em}%
190 }{%
191 \setlength{\@sepcolwidth}{\sepcolwidth}%
192 }
193
194 % maincolumn
195 \ifdimequal{\maincolwidth}{0pt}{%
196 \setlength{\@maincolwidth}{\komacvtextwidth-\@sepcolwidth-\@hintscolwidth}%
197 }{%
198 \setlength{\@maincolwidth}{\maincolwidth}%
199 }
200
201 % doubleitem
202 \ifdimequal{\dbitemmaincolwidth}{0pt}{%

```

```

203     \setlength{\@dbitemmaincolwidth}{%
204     \@maincolwidth-\@hintscolwidth-2\@sepcolwidth}%
205     \setlength{\@dbitemmaincolwidth}{0.5\@dbitemmaincolwidth}%
206 }{%
207     \setlength{\@dbitemmaincolwidth}{\dbitemmaincolwidth}%
208 }
209
210 % listitem
211 \ifdimequal{\listitemsymbolwidth}{Opt}{%
212     \settowidth{\@listitemsymbolwidth}{\listitemsymbol{}}~}%
213 }{%
214     \setlength{\@listitemsymbolwidth}{\listitemsymbolwidth}%
215 }
216     \setlength{\@listitemmaincolwidth}{\@maincolwidth-\@listitemsymbolwidth}%
217
218 % listdoubleitem
219 \ifdimequal{\listdbitemmaincolwidth}{Opt}{%
220     \setlength{\@listdbitemmaincolwidth}{\@maincolwidth-\@listitemsymbolwidth}%
221     \setlength{\@listdbitemmaincolwidth}{0.475\@listdbitemmaincolwidth}% %
222 }{%
223     \setlength{\@listdbitemmaincolwidth}{\listdbitemmaincolwidth}%
224     \setlength{\@listdbitemmaincolwidth}{0.475\@listdbitemmaincolwidth}% %
225 }
226
227 % quote
228 \ifdimequal{\quotewidth}{Opt}{%
229     \setlength{\@quotewidth}{0.65\textwidth}%
230 }{%
231     \setlength{\@quotewidth}{\quotewidth}%
232 }
233 \ifdimequal{\afterquotevspace}{Opt}{%
234     \setlength\@afterquotevspace{2\baselineskip}%
235 }{%
236     \setlength\@afterquotevspace{\afterquotevspace}%
237 }
238
239 % title
240 \ifundef{\@photoname}{% without picture:
241     \setlength\@aftertitlevspace{\aftertitlevspace}
242 }{% with picture:
243     \ifthenelse{%
244         \equal{\@photoframe}{frame} \OR
245         \equal{\@photoframe}{mframe}
246     }{% with frame:
247         \ifdimequal{\aftertitlevspace}{Opt}{%
248             \setlength\@aftertitlevspace{1.5\@fboxextra}
249         }{%
250             \setlength\@aftertitlevspace{\aftertitlevspace}
251         }
252     }{% without frame:

```

```

253         \setlength\@aftertitlevspace{\aftertitlevspace}
254     }%
255 }%
256 \ifundef{\@photoname}{}%
257     \ifdimequal{\titlesepwidth}{0pt}{%
258         \setlength\@titlesepwidth{\@sepcolwidth}
259     }{%
260         \setlength{\@titlesepwidth}{\titlesepwidth}
261     }
262 }
263
264 % afterelementsvspace
265 \ifdimequal{\afterelementsvspace}{0pt}{%
266     \setlength{\@afterelementsvspace}{0.25em}%
267 }{%
268     \setlength{\@afterelementsvspace}{\afterelementsvspace}%
269 }
270
271 % beforesecvspace
272 \ifdimequal{\beforesecvspace}{0pt}{%
273     \setlength{\@beforesecvspace}{3.5ex \@plus -1ex \@minus -.2ex}%
274 }{%
275     \setlength{\@beforesecvspace}{\beforesecvspace}%
276 }
277
278 % aftersecvspace
279 \ifdimequal{\aftersecvspace}{0pt}{%
280     \setlength{\@aftersecvspace}{2.3ex \@plus .2ex}%
281 }{%
282     \setlength{\@aftersecvspace}{\aftersecvspace}%
283 }
284 % beforesubsecvspace
285 \ifdimequal{\beforesubsecvspace}{0pt}{%
286     \setlength{\@beforesubsecvspace}{3.25ex \@plus -1ex \@minus -.2ex}%
287 }{%
288     \setlength{\@beforesubsecvspace}{\beforesubsecvspace}%
289 }
290
291 % aftersubsecvspace
292 \ifdimequal{\aftersubsecvspace}{0pt}{%
293     \setlength{\@aftersubsecvspace}{1.5ex \@plus .2ex}%
294 }{%
295     \setlength{\@aftersubsecvspace}{\aftersubsecvspace}%
296 }
297 } % end AtEndPreamble

```

Symbols

```

298 \providecommand*\@addresssymbol{}
299 \providecommand*\addresssymbol{}
300 \providecommand*\@mobilesymbol{\Mobilefone~}

```

```

301 \providecommand*\mobilesymbol{}
302 \providecommand*\phonesymbol{\Telefon~}
303 \providecommand*\phonesymbol{}
304 \providecommand*\faxsymbol{\FAX~}
305 \providecommand*\faxsymbol{}
306 \providecommand*\emailsymbol{\Letter~}
307 \providecommand*\emailsymbol{}
308 \providecommand*\homepagesymbol{}
309 \providecommand*\homepagesymbol{}
310 \providecommand*\twittersymbol{\faTwitter~}
311 \providecommand*\twittersymbol{}
312 \providecommand*\githubsymbol{\faGithub~}
313 \providecommand*\githubsymbol{}
314 \providecommand*\facebooksymbol{\faFacebook~}
315 \providecommand*\facebooksymbol{}
316 \providecommand*\linkedsymbol{\faLinkedin~}
317 \providecommand*\linkedsymbol{}
318 \providecommand*\@fsymbol{~~~\textbullet~~~}
319 \providecommand*\fsymbol{}
320 \providecommand*\@listitemsymbol{\textcolor{colortheme}{\Neutral}~}
321 \providecommand*\listitemsymbol{}
322
323 \AtEndPreamble{%
324   \ifdefempty{\addresssymbol}{}{%
325 \renewcommand*\@addresssymbol{\addresssymbol}
326   }
327   \ifdefempty{\mobilesymbol}{}{%
328 \renewcommand*\@mobilesymbol{\mobilesymbol}
329   }
330   \ifdefempty{\phonesymbol}{}{%
331 \renewcommand*\@phonesymbol{\phonesymbol}
332   }
333   \ifdefempty{\faxsymbol}{}{%
334 \renewcommand*\@faxsymbol{\faxsymbol}
335   }
336   \ifdefempty{\emailsymbol}{}{%
337 \renewcommand*\@emailsymbol{\emailsymbol}
338   }
339   \ifdefempty{\homepagesymbol}{}{%
340 \renewcommand*\@homepagesymbol{\homepagesymbol}
341   }
342   \ifdefempty{\twittersymbol}{}{%
343 \renewcommand*\@twittersymbol{\twittersymbol}
344   }
345   \ifdefempty{\githubsymbol}{}{%
346 \renewcommand*\@githubsymbol{\githubsymbol}
347   }
348   \ifdefempty{\facebooksymbol}{}{%
349 \renewcommand*\@facebooksymbol{\facebooksymbol}
350   }

```

```

351     \ifdefempty{\linkedinsymbol}{-}{%
352 \renewcommand*\@linkedinsymbol{\linkedinsymbol}
353 }
354     \ifdefempty{\fsymbol}{-}{%
355 \renewcommand*\@fsymbol{\fsymbol}
356 }
357     \ifdefempty{\listitemsymbol}{-}{%
358 \renewcommand*\@listitemsymbol{\listitemsymbol}
359 }
360
361
362 } % end \AtEndPreamble
363

```

Personal data

```

364     \providecommand*\{firstname}{-}{}
365     \providecommand*\{familyname}{-}{}
366     \providecommand*\{acadtitle}{-}{}
367     \providecommand*\{addressstreet}{-}{}
368     \providecommand*\{addresscity}{-}{}
369     \providecommand*\{address}[2]{\{addressstreet{#1}\addresscity{#2}}
370     \providecommand*\{mobile}{-}{}
371     \providecommand*\{phonenr}{-}{}
372     \providecommand*\{faxnr}{-}{}
373     \providecommand*\{email}{-}{}
374     \providecommand*\{homepage}{-}{}
375     \providecommand*\{extrainfo}{-}{}
376     \providecommand*\{cvquote}{-}{}

```

Itemize

With enumitem

```

377     \newlist{compactitem}{itemize}{3}
378     \newlist{compactenum}{enumerate}{3}
379     \newlist{compactdesc}{description}{3}
380     \setlist[compactitem,compactenum,compactdesc]{%
381     topsep=0pt,%
382     partopsep=0pt,%
383     itemsep=0pt,%
384     parsep=0pt,%
385     leftmargin=*%
386 } % end setlist
387     \AtEndPreamble{%
388     \setlist[compactitem,1]{label=\@listitemsymbol}
389     \setlist[compactitem,2]{label={\textcolor{colortheme}\textendash}}
390     \setlist[compactitem,3]{label={\textcolor{colortheme}\textperiodcentered}}
391     \setlist[compactenum,1]{label={\textcolor{colortheme}{\arabic*}}}
392     \setlist[compactenum,2]{label={\textcolor{colortheme}{\alph*}}}
393     \setlist[compactenum,3]{label={\textcolor{colortheme}{\roman*}}}
394     } % end AtEndPreamble

```

Picture

```
395 \newlength\@photowidth
396 \providecommand{\photo}[3] []{%
397   \providecommand{\@photoframe}{#1}%
398   \setlength{\@photowidth}{#2}%
399   \providecommand{\@photoname}{#3}}
```

Headline

```
400 \providecommand\headlinetype{none}
401 \providecommand\@headlinecontent{}
402 \providecommand\headlinecontent{}
403 \providecommand\headline[2]{\renewcommand\headlinecontent{#1}\renewcommand\headlinetype{#2}
404
405 \AtEndPreamble{%
406   \ifdefstring{\headlinetype}{name}{%
407     \ifdefempty{\headlinecontent}{%
408       \renewcommand*\@headlinecontent{\firstnamestyle{\firstname}\ familynamestyle{\familyname}
409         \ifdefempty{\acadtitle}{%
410           \par\bigskip\acadtitlestyle{\acadtitle}}%
411       }}{%
412       \renewcommand*\@headlinecontent{\headlinecontent}
413     }}{}
414   \ifdefstring{\headlinetype}{title}{%
415     \ifdefempty{\headlinecontent}{%
416       \renewcommand*\@headlinecontent{\headlinestyle{Curriculum Vitae}}
417     }{%
418       \renewcommand*\@headlinecontent{\headlinecontent}
419     }}{}
420   }
421   % \end{macrocode}
422   %
423   %\subsubsection*{Title/Head}
424   % \begin{macrocode}
425   \newif\if@firstdetailselement\@firstdetailselementtrue
426   \providecommand*{\@titledetailsnewline}{
427     \if@firstdetailselement%
428       \@firstdetailselementfalse%
429     \else%
430       \\.4ex]
431     \fi%
432   }
433   \renewcommand\maketitle{\csexpandonce{@cvttitle\komacv@style}}
```

Lastpage

```
434 \RequirePackage{lastpage}
435 \providecommand*\totalpagemark){% page and pagetotal
436 \usefonttokomafont{pagenumber}\pageref{LastPage}%
437 }
```

Element styles

```
438 \providecommand*\headlinestyle[1]{%
439 \usefontofkomafont{headlinefont}%
440 \textcolor{@headlinecolor}{#1}}
441 \providecommand*\firstnamestyle[1]{%
442 \usefonttokomafont{firstnamefont}%
443 \textcolor{@firstnamecolor}{#1}}
444 \providecommand*\familynamestyle[1]{%
445 \usefonttokomafont{familynamefont}%
446 \textcolor{@familynamecolor}{#1}}
447 \providecommand*\acadttitlestyle[1]{%
448 \usefonttokomafont{acadttitlefont}%
449 \textcolor{@acadttitlecolor}{#1}}
450 \providecommand*\addressstyle[1]{%
451 \usefonttokomafont{addressfont}%
452 \textcolor{@addresscolor}{#1}}
453 \providecommand*\quotestyle[1]{%
454 \usefonttokomafont{quote font}%
455 \textcolor{@quotecolor}{#1}}
456 \providecommand*\hintstyle[1]{%
457 \usefonttokomafont{hintfont}%
458 \textcolor{@hintcolor}{#1}}
459 \providecommand*\sectionstyle[1]{%
460 \usefonttokomafont{section}%
461 \textcolor{@seccolor}{#1}}
462 \providecommand*\subsectionstyle[1]{%
463 \usefonttokomafont{subsection}%
464 \textcolor{@subseccolor}{#1}}
```

Elements

cvitem

usage: \cvitem[*spacing*]{*header*}{*text*}

```
465 \providecommand*\cvitem[3][\@afterelements vspace]{%
466 \begin{tabular}{%
467 @{}p{@hintscolwidth}%
468 @{\hspace{@sepcolwidth}}p{@maincolwidth}@{}%
469 }%
470 \RaggedLeft\hintstyle{#2} &{#3}%
471 \end{tabular}\@[#1]%
472 }
```

cvdoubleitem

usage: \cvdoubleitem[*spacing*]{*header1*}{*text1*}{*header2*}{*text2*}

```
473 \providecommand*\cvdoubleitem[5][\@afterelements vspace]{%
474 \cvitem[#1]{#2}{%
475 \begin{minipage}[t]{\@dbitemmaincolwidth}#3\end{minipage}%
476 \hspace*{@sepcolwidth}%
477 \begin{minipage}[t]{\@hintscolwidth}%
478 \noindent\RaggedLeft\hintstyle{#4}
```

```

479     \end{minipage}%
480     \hspace*{\@sepcolwidth}%
481     \begin{minipage}[t]{\@dbitemmaincolwidth}%
482         \noindent #5
483     \end{minipage}%
484 }%
485 }

```

cvlistitem

usage: `\cvlistitem[⟨label⟩]{⟨item⟩}`

```

486     \providecommand*\cvlistitem[2][\@afterelements\svspace]{%
487         \cvitem[#1]{%
488             \@listitemsymbol%
489             \begin{minipage}[t]{\@listitemmaincolwidth}%
490                 #2%
491             \end{minipage}%
492         }%
493     }

```

cvlistdoubleitem

usage: `\cvlistdoubleitem[⟨label⟩]{⟨item1⟩}{⟨item2⟩}`

```

494     \providecommand*\cvlistdoubleitem[3][\@afterelements\svspace]{%
495         \cvitem[#1]{%
496             \@listitemsymbol%
497             \begin{minipage}[t]{\@listdbitemmaincolwidth}%
498                 #2%
499             \end{minipage}%
500             \hspace*{\@sepcolwidth}
501             \ifstrempy{#3}{%
502                 \@listitemsymbol%
503                 \begin{minipage}[t]{\@listdbitemmaincolwidth}%
504                     #3%
505                 \end{minipage}
506             }%
507         }%
508     }

```

cventry

usage: `\cventry[⟨spacing⟩]{⟨years⟩}{⟨degree/job title⟩}{⟨institution/employer⟩}{⟨localization⟩}{⟨grade/...⟩}{⟨comment/job description⟩}`

```

509     \providecommand*\cventry[7][\@afterelements\svspace]{%
510         \cvitem[#1]{#2}{%
511             {\bfseries#3}%
512             \ifstrempy{#4}{,}{\itshape#4}}%
513         \ifstrempy{#5}{,}{#5}%
514         \ifstrempy{#6}{,}{#6}%
515         .%
516         \ifx&#7&{%
517             \else{%

```

```

518         \newline{\begin{minipage}[t]{\linewidth}%
519             \small#7%
520         \end{minipage}}%
521     }%
522     \fi%
523 }%
524 }

```

cvitemwithcomment

usage: `\cvitemwithcomment` [*spacing*] {*header*} {*text*} {*comment*}

```

525     \newbox{\@commentmainbox}
526     \providecommand*\cvitemwithcomment[4][\@afterelements vspace]{%
527         \savebox{\@commentmainbox}{\usefonttokomafont{commentmainfont}#3}}%
528         \settoheight\@commentmainlength{\usebox{\@commentmainbox}}%
529         \setlength{\@commentlength}{%
530             \@maincolwidth-\@sepcolwidth-\@commentmainlength%
531         }%
532         \cvitem[#1]{#2}{%
533             \begin{minipage}[t]{\@commentmainlength}%
534                 \usefonttokomafont{commentmainfont} #3%
535             \end{minipage}}%
536         \hfill%
537         \begin{minipage}[t]{\@commentlength}%
538             \RaggedLeft\usefonttokomafont{commentfont} #4%
539         \end{minipage}}%
540     }%
541 }

```

link

usage: `\link` [*optional text*] {*link*}

```

542     \providecommand*\link[2][ ]{%
543         \ifstreampy{#1}{%
544             \href{#2}{\usefonttokomafont{linkfont}#2}}{%
545             \href{#2}{\usefonttokomafont{linkfont}#1}}%
546     }

```

httplink

usage: `\httplink` [*optional text*] {*link*}

```

547     \providecommand*\httplink[2][ ]{%
548         \ifstreampy{#1}{%
549             \href{http://#2}{\usefonttokomafont{httplinkfont}#2}}{%
550             \href{http://#2}{\usefonttokomafont{httplinkfont}#1}}%
551     }

```

emaillink

usage: `\emaillink` [*optional text*] {*link*}

```

552     \providecommand*\emaillink[2][ ]{%
553         \ifstreampy{#1}{%

```

```

554         \href{mailto:#2}{\usefonttokomafont{emallinkfont}#2}}{-%
555         \href{mailto:#2}{\usefonttokomafont{emallinkfont}#1}}}%
556     }

```

Sections

```

557     % Depending on the style in use (see style descriptions).

```

Hypersetup

```

558     \hypersetup{
559         breaklinks,
560         unicode,
561         colorlinks      = false,
562         pdfborder       = {0 0 .3},
563         pdfstartview   = FitH,
564         pdfstartpage   = 1,
565         pdfcreator      = \LaTeX{},
566         pdfproducer    = \LaTeX{}
567     }
568     \urlstyle{same}
569     \providecommand*\@citebordercolor{}
570     \providecommand*\citebordercolor{\@citebordercolor}
571     \providecommand*\@filebordercolor{}
572     \providecommand*\filebordercolor{\@filebordercolor}
573     \providecommand*\@linkbordercolor{}
574     \providecommand*\linkbordercolor{\@linkbordercolor}
575     \providecommand*\@menubordercolor{}
576     \providecommand*\menubordercolor{\@menubordercolor}
577     \providecommand*\@runbordercolor{}
578     \providecommand*\runbordercolor{\@runbordercolor}
579     \providecommand*\@urlbordercolor{}
580     \providecommand*\urlbordercolor{\@urlbordercolor}
581     \providecommand*\allbordercolors{}
582     \providecommand*\pdfauthor{}
583     \providecommand*\pdfsubject{}
584     \providecommand*\pdftitle{}
585     \providecommand*\pdfkeywords{}
586
587     \AtEndPreamble{%
588     \providecommand*\@allbordercolors{colortheme}
589     \ifdefempty{\allbordercolors}{}{\renewcommand*\@allbordercolors{\allbordercolors}}
590     \providecommand*\@pdfauthor{\firstname~\familyname}
591     \ifdefempty{\pdfauthor}{}{\renewcommand*\@pdfauthor{\pdfauthor}}
592     \providecommand*\@pdfsubject{\firstname~\familyname}
593     \providecommand*\pdfsubject{\@pdfsubject}
594     \providecommand*\@pdftitle{\title~\firstname~\familyname}
595     \providecommand*\pdftitle{\@pdftitle}
596     \providecommand*\@pdfkeywords{\firstname~\familyname{} curriculum~vit\ae{} CV{}}
597     \providecommand*\pdfkeywords{\@pdfkeywords}
598     \hypersetup{%

```

```

599     allbordercolors = \@allbordercolors,
600     citebordercolor = \citebordercolor,
601     filebordercolor = \filebordercolor,
602     linkbordercolor = \linkbordercolor,
603     menubordercolor = \menubordercolor,
604     runbordercolor = \runbordercolor,
605     urlbordercolor = \urlbordercolor,
606     pdfauthor = \@pdfauthor,
607     pdfsubject = \pdfsubject,
608     pdftitle = \pdftitle,
609     pdfkeywords = \pdfkeywords,
610   }
611 } % end AtEndPreamble

```

Varia

```

612 \AtBeginDocument{%
613   \raggedbottom
614 } % End AtBeginDocument
615 \clearscrheadfoot

```

Load style

```

616 \RequirePackage{komagcv-\komacv@style}

```

10.2 The classic style

Fonts

```

617 \addtokomafont{firstnamefont}{\sffamily}
618 \addtokomafont{acadtitlefont}{\sffamily}
619 \addtokomafont{addressfont}{\sffamily}
620 \addtokomafont{hintfont}{\sffamily}

```

Lengths

```

621 \AtEndPreamble{%
622   %\AtBeginDocument{
623   % mframepicshift
624   \ifdimequal{\mframepicshift}{0pt}{%
625     \setlength\@mframepicshift{.5\photowidth+\@fboxextra}
626   }{%
627     \setlength\@mframepicshift{\mframepicshift}
628   }
629 } % end \AtBeginDocument

```

Title / Head

```

630 \AtEndPreamble{%
631   \ifdimequal{\titlenamemaxwidth}{0pt}{%
632     \setlength{\@titlenamemaxwidth}{.525\textwidth}
633   }{
634     \setlength\@titlenamemaxwidth{\titlenamemaxwidth}
635   }
636 }

```

```

637 \providecommand\@cvttitleclassic{%
638 %% set \cs{@titlenamemaxwidth} to the full name length, capped by \cs{@titlenamemaxwidth}
639 \settowidth{\@titlenamefullwidth}{\firstnamestyle{\firstname}\familynamestyle{\familyname}}
640 \ifdimless{\@titlenamemaxwidth}{\@titlenamefullwidth}{%
641 \setlength{\@titlenamewidth}{\@titlenamemaxwidth}
642 }{%
643 \setlength{\@titlenamewidth}{\@titlenamefullwidth}
644 }
645 % set titlenamedetailwidth
646 \setlength{\@titledetailwidth}{\textwidth-\@titlenamewidth-\@titlesepwidth}%
647 \ifundef{\@photoframe}{\@titlesepwidth}{% else
648 \ifdefstring{\@photoframe}{frame}{%
649 \setlength{\@titledetailwidth}{\@titledetailwidth-\@photowidth-2\@fboxextra}
650 }{% else
651 \ifdefstring{\@photoframe}{mframe}{%
652 \setlength{\@titledetailwidth}{\@titledetailwidth-\@mframepicshift}%
653 }{%
654 }%
655 }%
656 % name and title
657 \ifdefstring{\headlinecontent}{none}{%
658 }{
659 \begin{center}
660 \headlinestyle{\@headlinecontent}\par\bigskip
661 \end{center}
662 }
663 \begin{minipage}[b]{\@titlenamewidth}%
664 \RaggedRight
665 \ifdefstring{\headlinecontent}{name}{\hfill\mbox{}}{%
666 \firstnamestyle{\firstname}\ %
667 \familynamestyle{\familyname}%
668 \ifdefempty{\acadtitle}{\@acadtitle}{%
669 \par\bigskip\acadtitlestyle{\acadtitle}}%
670 }
671 \end{minipage}%
672 % optional data
673 \begin{minipage}[b]{\@titledetailwidth}%
674 \RaggedLeft\addressstyle{%
675 \ifdefempty{\addressstreet}{\@addressstreet}{%
676 \@titledetailsnewline%
677 \@addresssymbol\addressstreet%
678 \ifdefempty{\addresscity}{\@addresscity}{%
679 \@titledetailsnewline\addresscity}}%
680 \ifdefempty{\mobile}{\@mobile}{%
681 \@titledetailsnewline\@mobilesymbol~\mobile}%
682 \ifdefempty{\phonenumber}{\@phonenumber}{%
683 \@titledetailsnewline\@phonesymbol~\phonenumber}%
684 \ifdefempty{\faxnr}{\@faxnr}{%
685 \@titledetailsnewline\@faxsymbol~\faxnr}%
686 \ifdefempty{\email}{\@email}{%

```

```

687         \@titledetailsnewline\@emailsymbolsymbol\emalink{\email}}%
688     \ifdefempty{\homepage}{-}{%
689         \@titledetailsnewline\@homepagesymbolsymbol\httplink{\homepage}}%
690     \ifdefempty{\extrainfo}{-}{%
691         \@titledetailsnewline\extrainfo}%
692     }%
693 \end{minipage}%
694 % optional photo
695 \ifundef{\@photoname}{-}{% with picture:
696     \hspace*{\@titlesepwidth}%
697     \ifthenelse{%
698         \equal{\@photoframe}{frame} \OR
699         \equal{\@photoframe}{mframe}
700     }{% with frame:
701         \begin{minipage}[b]{\@photowidth}%
702             \fcolorbox{@framecolor}{@framebackcolor}{%
703                 \includegraphics[width=\@photowidth]{\@photoname}}%
704         \end{minipage}}{% without frame:
705         \begin{minipage}[b]{\@photowidth}
706             \includegraphics[width=\@photowidth]{\@photoname}
707         \end{minipage}}
708 \\\[\@aftertitlevspace]
709 % optional quote
710 \ifundef{\cvquote}{-}{%
711     \centering
712     \begin{minipage}{\@quotewidth}%
713         \centering\quotestyle{\cvquote}%
714     \end{minipage}\\\[\@afterquotevspace]%
715 }%
716 }

```

Sections

```

717     \setcounter{secnumdepth}{1}
718
719     \RedeclareSectionCommand
720     [
721         beforeskip=\@beforesecvspace,
722         afterskip=\@aftersecvspace,
723         font=\color{@seccolor}
724     ]{section}
725     \renewcommand*\thesection{\color{@secbarcolor}\rule{\@hintscolwidth}{1ex}\hspace{-1ex}\hspace{1ex}}
726
727     \RedeclareSectionCommand
728     [
729         beforeskip=\@beforesecvspace,
730         afterskip=\@aftersecvspace,
731         indent=\dimexpr\@sepcolwidth+\@hintscolwidth,
732         font={\normalfont\color{@subseccolor}}
733     ]{subsection}

```

Elements

As defined by the class.

10.3 The casual style

Fonts

```
734 \addtokomafont{firstnamefont}{\sffamily\fontsize{38}{40}}
735 \addtokomafont{acadtitlefont}{\sffamily}
736 \addtokomafont{addressfont}{\sffamily\small}
737 \addtokomafont{hintfont}{\sffamily}
```

Footer

```
738 \newsavebox\@fboxa
739 \newsavebox\@fboxb
740 \providecommand*\@sboxa[1]{\sbox\@fboxa{#1}}
741 \providecommand*\@sboxb[1]{\sbox\@fboxb{#1}}
742 \providecommand*\@uboxa{\usebox\@fboxa}
743 \providecommand*\@uboxb{\usebox\@fboxb}
744 \providecommand*\@flushf{\strut\@uboxa\@sboxa{}\@sboxb{}}
745 \providecommand*\addtofooter[2][\@fssymbol]{%
746   \@sboxb{\@uboxa{#1#2}}%
747   \settowidth\@fboxwidth{\@uboxb}%
748   \ifdimgreater{\@footerwidth}{\@fboxwidth}{%
749     \@sboxa{\@uboxb}
750   }{%
751     \@flushf\@
752     \@sboxa{#2}
753     \@sboxb{#2}
754   }
755 }
756 \ifdimequal{\footerwidth}{0pt}{\setlength\@footerwidth{\footerwidth}}
757 \defpagestyle{footer}
758 {}{}{}% head definition (empty)
759 {% foot definition
760 {}{}% definition for twoside layout
761 {}{}% definition for oneside layout
762 \hspace*\fill}%
763 \parbox{\@footerwidth}{%
764   \centering%
765   \color{\@addresscolor}\usefonttokomafont{addressfont}%
766   \ifdefempty{\addressstreet}{}{}%
767   \addtofooter[]{\@addresssymbol\addressstreet}%
768   \ifdefempty{\addresscity}{}{}%
769   \addtofooter[~--~]{\addresscity}}}%
770 \ifdefempty{\mobile}{}{}%
771 \addtofooter{\@mobilesymbol\mobile}}%
772 \ifdefempty{\phonenumber}{}{}%
773 \addtofooter{\@phonesymbol\phonenumber}}
774 \ifdefempty{\faxnr}{}{}%
```

```

775         \addtofooter{\@faxsymbol\faxnr}}%
776     \ifdefempty{\email}{-}{%
777         \addtofooter{\@emailsymbolsymbol\emailink{\email}}%
778     \ifdefempty{\homepage}{-}{%
779         \addtofooter{\@homepagesymbolsymbol\httplink{\homepage}}}%
780     \ifdefempty{\extrainfo}{-}{%
781         \addtofooter{\extrainfo}}\@flushf%
782     }% Ende parbox
783     \hspace*{\fill}%
784     \makebox[0pt][r]{\pagemark/\totalpagemark}
785     }% end definition onesided layout
786 }% end footer definition

```

Head / title

```

787 \providecommand\@cvttitlecasual{%
788 \newbox{\@picbox}
789 \savebox{\@picbox}{%
790     \ifundef{\@photoname}{-}{% with picture:
791         \ifthenelse{%
792             \equal{\@photoframe}{frame} \OR
793             \equal{\@photoframe}{mframe}
794         }{% with frame:
795             \fcolorbox{\@framecolor}{\@framebackcolor}{%
796                 \includegraphics[width=\@photowidth]{\@photoname}%
797             }% end fcolorbox
798         }{% without frame:
799             \includegraphics[width=\@photowidth]{\@photoname}%
800         }% end ifdefstring frame
801     }% end ifundef photoname
802 }% end savebox picbox
803 \settowidth\@titlepicwidth{\usebox{\@picbox}}
804 \setlength\@titlenamewidth{\textwidth-\@titlesepwidth-\@titlepicwidth}
805
806 \usebox{\@picbox}%
807 \hspace*{\@titlesepwidth}%
808 \parbox[b]{\@titlenamewidth}{%
809     \RaggedLeft{\firstnamestyle\firstname}%
810     ~{\familynamestyle\familyname}\
811     \RaggedLeft\color{\@firstnamecolor}\rule{\@titlenamewidth}{.25ex}\par
812 }% end parbox
813 \vspace{\@aftertitlevspace}
814 %% optional acadtitle
815 \ifdefempty{\acadtitle}{-}{%
816     \RaggedLeft\acadtitlestyle{\acadtitle}}\@aftertitlevspace}%
817 %% optional quote
818 \ifdefempty{\cvquote}{-}{%
819     {centering
820         \begin{minipage}{\@quotewidth}%
821             \centering\quotestyle{\cvquote}
822         \end{minipage}}\@afterquotevspace}%

```

```

823     }
824     }%
825 }% end \@cvtitle-casual
826
827 \AtBeginDocument{%
828   \thispagestyle{footer}
829 } % end \AtBeginDocument

```

Sections

```

830 \setcounter{secnumdepth}{1}
831
832 \RedeclareSectionCommand
833 [
834   beforeskip=\@beforesecvspace,
835   afterskip=\@aftersecvspace,
836   font=\color{@seccolor}
837 ]{section}
838 \renewcommand*{thesection}{\color{secbarcolor}\rule{@hintscolwidth}{1ex}\hspace{-1ex}\hsp
839
840 \RedeclareSectionCommand
841 [
842   beforeskip=\@beforesecvspace,
843   afterskip=\@aftersecvspace,
844   indent=\dimexpr\@sepcolwidth+\@hintscolwidth,
845   font={\normalfont\color{@subseccolor}}
846 ]{subsection}

```

10.4 The oldstyle style

Lengths

```

847 \KOMAOptions{DIV=15}
848 \setlength{\hintscolwidth}{3cm}

```

Fonts

```

849 \addtokomafont{addressfont}{\small}
850 \addtokomafont{hintfont}{\bfseries}
851 \setkomafont{section}{\Large\bfseries\upshape}
852 \setkomafont{subsection}{\large\bfseries\itshape}

```

Colors

```

853 \colorlet{addresscolor}{gray}

```

Symbols

```

854 \renewcommand*{\listitemsymbol}{\labelitemi~}
855 \renewcommand*{\addresssymbol}{~}
856 \renewcommand*{\mobilesymbol}{\textbf{M}~}
857 \renewcommand*{\phonesymbol}{\textbf{T}~}
858 \renewcommand*{\faxsymbol}{\textbf{F}~}
859 \renewcommand*{\emailsymbolsymbol}{\textbf{E}~}
860 \renewcommand*{\homepagesymbol}{~}

```

Infocolumn and title

```
861 \setlength{\infocolwidth}{3.5cm}
862 \setlength{\sepinfocolwidth}{2em}
863
864 \providecommand\@infocontent{%
865 \ifdefempty{\addressstreet}{-}{%
866 \@titledetailsnewline%
867 \@addresssymbol\addressstreet%
868 \ifdefempty{\addresscity}{-}{%
869 \@titledetailsnewline\addresscity}}%
870 \ifdefempty{\mobile}{-}{%
871 \@titledetailsnewline\@mobilesymbol~\mobile}%
872 \ifdefempty{\phonenr}{-}{%
873 \@titledetailsnewline \@phonesymbol\phonenr}%
874 \ifdefempty{\faxnr}{-}{%
875 \@titledetailsnewline\@faxsymbol\faxnr}%
876 \ifdefempty{\email}{-}{%
877 \@titledetailsnewline\@emailsymbols\emallink{\email}}%
878 \ifdefempty{\homepage}{-}{%
879 \@titledetailsnewline\@homepagesymbols\httplink{\homepage}}%
880 \ifdefempty{\extrainfo}{-}{%
881 \@titledetailsnewline\extrainfo}%
882 } % end \@infocontent
883
884 \providecommand{\@makeinfo}{%
885 \newbox{\@infobox}%
886 \savebox{\@infobox}{%
887 \parbox[b]{\@infocolwidth}{%
888 % put the first line on the same baseline as the first sectiontitle:
889 {\usefonttokomafont{section}
890 \vspace*{1.6ex}
891 }
892 \RaggedLeft\addressstyle{%
893 \@infocontent%
894 }
895 }% end parbox
896 } % end savebox \@infobox%
897 \newlength{\@infoheight}%
898 \setlength{\@infoheight}{%
899 \totalheightof{\usebox{\@infobox}}%
900 }%
901 \usebox{\@infobox}\vspace*{-\@infoheight}%
902 \par\nointerlineskip%
903 \vspace*{-\parskip}%
904 \vspace*{-\@afterseccvspace}
905 }% end \providecommand \@makeinfo
906
907 \providecommand{\@cvttitleoldstyle}{%
908 % optional picture box
```

```

909     \newbox{\@picbox}
910     \savebox{\@picbox}{%
911     \ifundef{\@photoname}{}{% with picture:
912     \ifthenelse{%
913     \equal{\@photoframe}{frame} \OR
914     \equal{\@photoframe}{mframe}
915     }{% with frame:
916     \fcolorbox{@framecolor}{@framebackcolor}{%
917     \includegraphics[width=\@photowidth]{\@photoname}%
918     }% end fcolorbox
919     }{% without frame:
920     \includegraphics[width=\@photowidth]{\@photoname}%
921     }% end ifdefstring frame
922     }% end ifundef photoname
923     }% end savebox picbox
924     \settowidth\@titlepicwidth{\usebox{\@picbox}}
925     \setlength\@titlenamewidth{\textwidth-\@titlesepwidth-\@titlepicwidth}
926     \begin{minipage}[b]{\@titlenamewidth}%
927     \firstnamestyle{\firstname}\ %
928     \familynamestyle{\familyname}%
929     \ifdefempty{\acadtitle}{}{%
930     \[1.25em]\acadtitlestyle{\acadtitle}}%
931     \end{minipage}%
932     % optional photo
933     \usebox{\@picbox}%
934     \[\@aftertitlevspace]%
935     % optional quote
936     \ifdefempty{\cvquote}{}{%
937     {\centering%
938     \begin{minipage}{\@quotewidth}%
939     \centering\quotestyle{\cvquote}%
940     \end{minipage}}\[\@afterquotevspace]%
941     }%
942     }%
943     % address info box
944     \@makeinfo
945     \par
946     \begin{addmargin}[\komacvinfoleextrawidth]{Opt}
947     } % end \@cvttitleoldstyle
948
949     \AtEndDocument{%
950     \end{addmargin}
951     }

```

Sections

```

952     \setcounter{secnumdepth}{0}
953
954     \RedeclareSectionCommand
955     [
956     beforekip=\@beforesecvspace,

```

```

957     afterskip=\@aftersecvspace,
958     indent=\dimexpr\@sepcolwidth+\@hintscolwidth,
959     font=\color{@seccolor}
960   ]{section}
961
962   \RedeclareSectionCommand
963   [
964     beforeskip=\@beforesecvspace,
965     afterskip=\@aftersecvspace,
966     font=\color{@subseccolor}
967   ]{subsection}

```

Elements

```

968   \renewcommand*{\cvitem}[3][\@afterelementsospace]{%
969     \begin{tabular}{%
970       @{}p{\@maincolwidth}%
971       @{\hspace{\@sepcolwidth}}p{\@hintscolwidth}@{}%
972     }%
973     {#3} & \RaggedRight\hintstyle{#2}%
974   \end{tabular}\@#1%
975   }
976
977   \renewcommand*{\cvdoubleitem}[5][\@afterelementsospace]{%
978     \cvitem[#1]{#4}{%
979       \begin{minipage}[t]{\@dbitemmaincolwidth}#3\end{minipage}%
980       \hspace*{\@sepcolwidth}%
981       \begin{minipage}[t]{\@hintscolwidth}%
982         \noindent\RaggedLeft\hintstyle{#2}
983       \end{minipage}%
984       \hspace*{\@sepcolwidth}%
985       \begin{minipage}[t]{\@dbitemmaincolwidth}%
986         \noindent #5
987       \end{minipage}%
988     }%
989   }

```

Change History

v1.0	
General: Initial version	1
v1.0.1	
General: Installation problem fixed	1
v1.1	
\headline: Default font size changed, due to new font <code>headlinefont</code>	4
New macro <code>headline</code> , and new correspondent elements	
<code>headlinestyle</code> , <code>headlinecolor</code> , <code>headlinefont</code>	4
General: <code>\usefonttokomafont</code> instead of <code>\usekomafont</code> , avoiding	
unintended side effects	13
Added macros and symbols for social media	17

Definition of <code>\section</code> and <code>\subsection</code> changed, mainly to avoid pagebreaks (all styles)	27
Lengths <code>\beforeseccvspace</code> , <code>\afterseccvspace</code> , <code>\beforesubseccvspace</code> and <code>\aftersubseccvspace</code> added to <code>\section</code> and <code>\subsection</code> definitions	24
Linebreaks (hyphenation and no justification in narrow lines) improved with <code>ragged2e</code>	12
New user length <code>\titlenamewidth</code>	13
Option headline added; user length <code>\titlenamewidth</code> ; behavior of sections and subsections improved; several bugfixes	1
<code>scrpage</code> instead of the obsolete <code>scrpage2</code>	12
Vertical space between name and academic title adjusted	20

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	
<code>\@addresssymbol</code>	<code>\@fsymbol</code> 318, 355, 745
. . . . 298, 325, 677, 767, 867	<code>\@githubsymbol</code> 312, 346
<code>\@afterelementsvspace</code>	<code>\@headlinecontent</code>
154, 266, 268, 465, 473,	401, 408, 412, 416, 418, 660
486, 494, 509, 526, 968, 977	<code>\@hintscolwidth</code> 96, 182, 184,
<code>\@afterquotevspace</code>	196, 204, 467, 477, 725,
151, 234, 236, 714, 822, 940	731, 838, 844, 958, 971, 981
<code>\@aftersecvspace</code>	<code>\@homepagesymbol</code>
. . . . 159, 280, 282, 722, 308, 340, 689, 779, 879
730, 835, 843, 904, 957, 965	<code>\@ifundefinedcolor</code>
<code>\@aftersubsecvspace</code> 165, 293, 295 35, 38, 41, 44,
<code>\@aftertitlevspace</code> 148, 241,	47, 50, 53, 56, 59, 62, 65, 68
248, 250, 253, 708, 813, 934	<code>\@infobox</code> 885, 886, 896, 899, 901
<code>\@allbordercolors</code> 588, 589, 599	<code>\@infocolwidth</code> 136, 171, 173, 887
<code>\@beforesecvspace</code>	<code>\@infocontent</code> 864, 882, 893
. 156, 273, 275,	<code>\@infoheight</code> 897, 898, 901
721, 729, 834, 842, 956, 964	<code>\@komacvtextwidth</code>
<code>\@beforesubsecvspace</code> 95, 174, 182, 196
. 162, 286, 288	<code>\@linkbordercolor</code> 573, 574
<code>\@citebordercolor</code> 569, 570	<code>\@linkedinesymbol</code> 352
<code>\@commentlength</code> . . 129, 529, 537	<code>\@linkedinsymbol</code> 316
<code>\@commentmainbox</code> . 525, 527, 528	<code>\@listdbitemmaincolwidth</code> . .
<code>\@commentmainlength</code> 117,
. 128, 528, 530, 533	220, 221, 223, 224, 497, 503
<code>\@cvttitle</code> 825	<code>\@listitemmaincolwidth</code> . . .
<code>\@cvttitlecasual</code> 787 114, 216, 489
<code>\@cvttitleclassic</code> 637	<code>\@listitemsymbol</code>
<code>\@cvttitleoldstyle</code> 907, 947	320, 358, 388, 488, 496, 502
<code>\@dbitemmaincolwidth</code>	<code>\@listitemsymbolwidth</code>
. 108, 203, 111, 212, 214, 216, 220
205, 207, 475, 481, 979, 985	<code>\@maincolwidth</code> 102, 196, 198,
<code>\@emailsvsymbol</code>	204, 216, 220, 468, 530, 970
. . . . 306, 337, 687, 777, 877	<code>\@makeinfo</code> 884, 905, 944
<code>\@facebookvsymbol</code> 314, 349	<code>\@menubordercolor</code> 575, 576
<code>\@faxvsymbol</code> 304, 334, 685, 775, 875	<code>\@mframepicshift</code>
<code>\@fbvboxextra</code> 177, 178, 248, 625, 649 125, 625, 627, 652
<code>\@fbvboxwidth</code> 145, 747, 748	<code>\@mobilevsymbol</code>
<code>\@filebordercolor</code> 571, 572 300, 328, 681, 771, 871
<code>\@firstdetailvelementfalse</code> 428	<code>\@pdfauthor</code> 590, 591, 606
<code>\@firstdetailvelementtrue</code> . 425	<code>\@pdfkeywords</code> 596, 597
<code>\@flushf</code> 744, 751, 781	<code>\@pdfsubject</code> 592, 593
<code>\@footerwidth</code>	<code>\@pdftitle</code> 594, 595
. . . . 143, 144, 748, 756, 763	<code>\@phonesvsymbol</code>
 302, 331, 683, 773, 873

<code>\definecolor</code>	30	<code>\hintstyle</code>	456, 470, 478, 973, 982
<code>\defpagestyle</code>	757	<code>\homepage</code>	374,
<code>\dimexpr</code>	731, 844, 958		688, 689, 778, 779, 878, 879
E		<code>\homepagesymbol</code>	309, 339, 340, 860
<code>\email</code>	373,	<code>\httplink</code> ...	547, 689, 779, 879
	686, 687, 776, 777, 876, 877	<code>\Huge</code>	79
<code>\emailink</code> ..	552, 687, 777, 877	<code>\hypersetup</code>	558, 598
<code>\emailsymbol</code> ..	307, 336, 337, 859	I	
<code>\extrainfo</code>	375,	<code>\includegraphics</code>	
	690, 691, 780, 781, 880, 881		703, 706, 796, 799, 917, 920
F		<code>\infocolwidth</code>	137, 138, 171, 861
<code>\facebooksymbol</code> ..	315, 348, 349	K	
<code>\faFacebook</code>	314	<code>\komacv@color</code>	33
<code>\faGithub</code>	312	<code>\komacv@style</code>	433, 616
<code>\faLinkedin</code>	316	<code>\komacv@xcolor</code>	15
<code>\familyname</code> ..	365, 408, 590, 592,	<code>\komacv@xcolwidth</code> ..	
	594, 596, 639, 667, 810, 928		142, 173, 174, 946
<code>\familynamestyle</code>		<code>\KOMAOptions</code>	847
	408, 444, 639, 667, 810, 928	L	
<code>\faTwitter</code>	310	<code>\labelitemi</code>	854
<code>\faxnr</code>	372,	<code>\link</code>	542
	684, 685, 774, 775, 874, 875	<code>\linkbordercolor</code>	574, 602
<code>\faxsymbol</code> ..	305, 333, 334, 858	<code>\linkedinsymbol</code> ..	317, 351, 352
<code>\fboxrule</code>	178	<code>\listdbitemmaincolwidth</code> ..	
<code>\fboxsep</code>	178		118, 119, 219, 223
<code>\fcolorbox</code>	702, 795, 916	<code>\listitemmaincolwidth</code> ..	115, 116
<code>\filebordercolor</code>	572, 601	<code>\listitemsymbol</code>	
<code>\firstname</code> ..	364, 408, 590, 592,		212, 321, 357, 358, 854
	594, 596, 639, 666, 809, 927	<code>\listitemsymbolwidth</code>	
<code>\firstnamestyle</code>			112, 113, 211, 214
	408, 441, 639, 666, 809, 927	M	
<code>\fontsize</code>	78, 734	<code>\maincolwidth</code>	103, 104, 195, 198
<code>\footerwidth</code>	146, 147, 756	<code>\maketitle</code>	433
<code>\footnotesize</code>	89	<code>\mbox</code>	665
<code>\fsymbol</code>	319, 354, 355	<code>\menubordercolor</code>	576, 603
G		<code>\mframepicshift</code>	126, 127, 624, 627
<code>\githubsymbol</code>	313, 345, 346	<code>\mobile</code>	370,
H			680, 681, 770, 771, 870, 871
<code>\headline</code>	1, 403	<code>\mobilesymbol</code>	301, 327, 328, 856
<code>\headlinecontent</code>		<code>\mycolor</code>	1, 33, 34
	402, 403, 407, 412, 415, 418	N	
<code>\headlinestyle</code> ...	416, 438, 660	<code>\newkomafont</code>	78–89
<code>\headlinetype</code>		<code>\normalfont</code>	732, 845
	400, 403, 406, 414, 657, 665	P	
<code>\hintscolwidth</code>		<code>\pagemark</code>	784
	97, 98, 181, 184, 848		

