

Tabulars with reledmac

Sommario

This file provides example of using tabular environments with *reledmac*.

We use `edtabularl`, `edtabularc` and `edtabularr`, with marginal, critical and familiar notes. We also use optional arguments of `\pstart`.

1 Left align

1	linea prima	linea prima	sidenote l
2	linea secunda	linea secunda ¹	sidenote l
3	linea tertia	linea tertia	sidenote l
4	linea quarta	linea quarta	
5	linea quinta	linea quinta ¹	
6	linea sexta	linea sexta	
7			

2 Center align

8	linea prima	linea prima	
9	linea secunda	linea secunda ²	sidenote c
10	linea tertia	linea tertia	sidenote c
11	linea quarta	linea quarta	sidenote c
12	linea quinta	linea quinta ²	
13	linea sexta	linea sexta	
14			

¹familiar footnote A.

²familiar footnote A.

¹familiar footnote B.

²familiar footnote B.

3 tertia] critical note A
10 tertia] critical note A

4 quarta] critical note B
11 quarta] critical note B

3 Right align

¹⁵ sidenote ⁶	linea prima	linea prima
sidenote ⁷	linea secunda	linea secunda ³
sidenote ⁸	linea tertia	linea tertia
¹⁹	linea quarta	linea quarta
²⁰	linea quinta	linea quinta ³
²¹	linea sexta	linea sexta

³familiar footnote A.

³familiar footnote B.

¹⁷ tertia] critical note A

¹⁸ quarta] critical note B