

The l3str-format package: formatting strings of characters

The L^AT_EX3 Project*

Released 2019-03-05

1 Format specifications

In this module, we introduce the notion of a string $\langle format \rangle$. The syntax follows that of Python's `format` built-in function. A $\langle format specification \rangle$ is a string of the form

$$\langle format specification \rangle = [[\langle fill \rangle]\langle alignment \rangle][\langle sign \rangle][\langle width \rangle][.\langle precision \rangle][\langle style \rangle]$$

where each [...] denotes an independent optional part.

- $\langle fill \rangle$ can be any character: it is assumed to be present whenever the second character of the $\langle format specification \rangle$ is a valid $\langle alignment \rangle$ character.
- $\langle alignment \rangle$ can be < (left alignment), > (right alignment), ^ (centering), or = (for numeric types only).
- $\langle sign \rangle$ is allowed for numeric types; it can be + (show a sign for positive and negative numbers), - (only put a sign for negative numbers), or a space (show a space or a -).
- $\langle width \rangle$ is the minimum number of characters of the result: if the result is naturally shorter than this $\langle width \rangle$, then it is padded with copies of the character $\langle fill \rangle$, with a position depending on the choice of $\langle alignment \rangle$. If the result is naturally longer, it is not truncated.
- $\langle precision \rangle$, whose presence is indicated by a period, can have different meanings depending on the type.
- $\langle style \rangle$ is one character, which controls how the given data should be formatted. The list of allowed $\langle styles \rangle$ depends on the type.

The choice of $\langle alignment \rangle =$ is only valid for numeric types: in this case the padding is inserted between the sign and the rest of the number.

*E-mail: latex-team@latex-project.org

2 Formatting various data-types

<code>\tl_format:Nn</code> *	<code>\tl_format:nn</code> $\{\langle token\ list\rangle\}$ $\{\langle format\ specification\rangle\}$
<code>\tl_format:cn</code> *	Converts the $\langle token\ list\rangle$ to a string according to the $\langle format\ specification\rangle$. The $\langle style\rangle$, if present, must be s . If $\langle precision\rangle$ is given, all characters of the string representation of the $\langle token\ list\rangle$ beyond the first $\langle precision\rangle$ characters are discarded.
<code>\tl_format:nn</code> *	

<code>\seq_format:Nn</code> *	<code>\seq_format:Nn</code> $\{\langle sequence\rangle\}$ $\{\langle format\ specification\rangle\}$
<code>\seq_format:cn</code> *	Converts each item in the $\langle sequence\rangle$ to a string according to the $\langle format\ specification\rangle$, and concatenates the results.

<code>\int_format:nn</code> *	<code>\int_format:nn</code> $\{\langle intexpr\rangle\}$ $\{\langle format\ specification\rangle\}$
	Evaluates the $\langle integer\ expression\rangle$ and converts the result to a string according to the $\langle format\ specification\rangle$. The $\langle precision\rangle$ argument is not allowed. The $\langle style\rangle$ can be b for binary output, d for decimal output (this is the default), o for octal output, X for hexadecimal output (using capital letters).

<code>\fp_format:nn</code> *	<code>\fp_format:nn</code> $\{\langle fpexpr\rangle\}$ $\{\langle format\ specification\rangle\}$
	Evaluates the $\langle floating\ point\ expression\rangle$ and converts the result to a string according to the $\langle format\ specification\rangle$. The $\langle precision\rangle$ defaults to 6. The $\langle style\rangle$ can be <ul style="list-style-type: none">• e for scientific notation, with one digit before and $\langle precision\rangle$ digits after the decimal separator, and an integer exponent, following e;• f for a fixed point notation, with $\langle precision\rangle$ digits after the decimal separator and no exponent;• g for a general format, which uses style f for numbers in the range $[10^{-4}, 10^{\langle precision\rangle})$ and style e otherwise.

3 Possibilities, and things to do

- Provide a token list formatting $\langle style\rangle$ which keeps the last $\langle precision\rangle$ characters rather than the first $\langle precision\rangle$.

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

F

fp commands:

`\fp_format:nn` 2

I

int commands:

`\int_format:nn` 2

	S		T
seq commands:		tl commands:	
\seq_format:Nn	2	\tl_format:Nn	2
		\tl_format:nn	2