



ConTeXt

commands

EN

ConTeXt

commands

en / english
August 5, 2008

`\about {1.1.} [2...]`

- 1 TEXT
- 2 REFERENCE

`\adaptlayout [...,1...] [...,2...,...]`
OPTIONAL

- 1 NUMBER
- 2 `height = DIMENSION max`
`lines = NUMBER`

`\appendix [...,1...] {2...}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\at {1...} {2...} [3...]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\atpage [1...]`

- * REFERENCE

`\background {1...}`

- * TEXT

`\blackrule [...,*...,...]`
OPTIONAL

- * *inherits from \setupblackrules*

`\blackrules [...,*...,...]`

- * *inherits from \setupblackrules*

`\blank [...,*...,...]`
OPTIONAL

- * `small medium big nowhite back white disable force reset line halfline FORMULA fixed flexible none`
`always outer joinedup`

`\bookmark [1...] {2...}`
OPTIONAL

- 1 IDENTIFIER
- 2 TEXT

`\but [1...]`

- * REFERENCE

`\button [...,1.,...] {...2.} [...3,...]`
OPTIONAL

- 1 *inherits from* \setupbuttons
- 2 TEXT
- 3 REFERENCE

`\bypassblocks [...,1,...] [...2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\cap {...}`

- * TEXT

`\CAP {...}`

- * TEXT

`\Cap {...}`

- * TEXT

`\Caps {...*...}`

- * WORD

`\chapter [...,1,...] {...2.}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\character {...}`

- * TEXT

`\Character {...}`

- * TEXT

`\Characters {...}`

- * TEXT

`\characters {...}`

- * TEXT

`\chem {1.} {2.} {3.}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\clip [...,1,...] {2.}`
OPTIONAL

- 1 *inherits from* \setupclipping
- 2 TEXT

`\clonefield [1.] [...,2,...] [3.] [...,4,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 IDENTIFIER
- 4 IDENTIFIER

`\color [1.] {2.}`

- 1 TEXT
- 2 TEXT

`\column`

`\comment [1.] [...,2,...] {3.}`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcomment
- 3 TEXT

`\comparecolorgroup [...]`

- * IDENTIFIER

`\comparepalet [...]`

- * IDENTIFIER

`\completeCOMBINEDLIST [1.] [...,2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcombinedlist

`\completelistofFLOATS`

`\completelistofSORTS`

`\completelistofSYNONYMS`

`\completeREGISTER [...,.*,...]`
OPTIONAL

* inherits from \setupregister

`\convertnumber {..} {..}`

1 TEXT

2 TEXT

`\copyfield [..] [...,2...]`

1 IDENTIFIER

2 IDENTIFIER

`\correctwhitespace {...}`

* TEXT

`\coupledocument [..] [..2] [..3]`

1 IDENTIFIER

2 file

3 IDENTIFIER

`\coupledREGISTER [..1] {..2}`
OPTIONAL

1 TEXT

2 ENTRY

`\couplemarking [..1] [..2]`

1 IDENTIFIER

2 IDENTIFIER

`\couplepage [...,1...] [...,2...]`

1 IDENTIFIER

2 option = doublesided
before = COMMAND
after = COMMAND

`\couplepaper [...]`

* IDENTIFIER

`\coupleregister [...]`

* IDENTIFIER

`\crlf`

`\currentdate [...,*,...]`

* *inherits from* \date

`\currentheadnumber`

`\date [...,1,...] [...,2,...]`
 OPTIONAL OPTIONAL

1 d = NUMBER
 m = NUMBER
 y = NUMBER

2 day month year weekday d m y w dd mm yy space -- day+ d+ dd+ referral TEXT

`\decouplemarking [...]`

* IDENTIFIER

`\define [1] \.2.. {3..}`
 OPTIONAL

1 NUMBER

2 NAME

3 TEXT

`\defineblank [1] [2..]`

1 IDENTIFIER

2 *inherits from* \setupblank

`\defineblock [...]`

* IDENTIFIER

`\definebodyfont [...,1,...] [2..] [...,3,,...]`

1

2 rm ss tt mm hw cg

3 tf = FILE

 bf = FILE

 sl = FILE

 it = FILE

 bs = FILE

 bi = FILE

 sc = FILE

 ex = FILE

 mi = FILE

 sy = FILE

 ma = FILE

 mb = FILE

 mc = FILE

```
\definebodyfontenvironment [1.] [2.] [3.,.,.]
                        OPTIONAL OPTIONAL OPTIONAL
```

```
1 IDENTIFIER
2 5pt ... 12pt default
3 text      = DIMENSION
  script    = DIMENSION
  scriptscript = DIMENSION
  x         = DIMENSION
  xx        = DIMENSION
  small     = DIMENSION
  big       = DIMENSION
```

```
\definebuffer [...]
```

```
* IDENTIFIER
```

```
\definecolor [1.] [2.,.,.]
```

```
1 IDENTIFIER
2 r = TEXT
  g = TEXT
  b = TEXT
  c = TEXT
  m = TEXT
  y = TEXT
  k = TEXT
  s = TEXT
  h = TEXT
  t = TEXT
  a = TEXT
  p = TEXT
  e = TEXT
```

```
\definecolorgroup [1.] [2.] [x:y:z=,.]
                        OPTIONAL
```

```
1 IDENTIFIER
2 rgb cmyk gray s
3 TRIPLET
```

```
\definecombinedlist [1.] [...2,...] [...3.,.,.]
                        OPTIONAL
```

```
1 IDENTIFIER
2 LIST
3 inherits from \setupcombinedlist
```

```
\defineconversion [1.] [2.]
```

```
1 IDENTIFIER
2 COMMAND TEXT
```

```
\definedescription [1.] [...2.,.,.]
                        OPTIONAL
```

```
1 IDENTIFIER
2 inherits from \setupdescriptions
```

```
\defineenumeration [...1,...] [...2.] [...,3.,...]  
                                OPTIONAL      OPTIONAL  
1  IDENTIFIER  
2  IDENTIFIER  
3  inherits from \setupenumerations
```

```
\definefield [...1.] [...2.] [...3.] [...,4,...] [...5.]  
                                           OPTIONAL  
1  IDENTIFIER  
2  text line  push  check  radio  combo  choice  popup  
3  IDENTIFIER  
4  IDENTIFIER  
5  IDENTIFIER
```

```
\definefieldstack [...1.] [...2,...] [...,3.,...]  
1  IDENTIFIER  
2  IDENTIFIER  
3  inherits from \setupfields
```

```
\definefiguresymbol [...1.] [...2.] [...,3.,...]  
                                OPTIONAL  
1  IDENTIFIER  
2  TEXT  
3  inherits from \setupexternalfigures
```

```
\definefloat [...1.] [...2.]  
1  SINGULAR NAME  
2  PLURAL NAME
```

```
\definefont [...1.] [...2.]  
1  IDENTIFIER  
2  FILE
```

```
\defineframed [...1.] [...,2.,...]  
                                OPTIONAL  
1  IDENTIFIER  
2  inherits from \setupframedtexts
```

```
\defineframedtext [...1.] [...,2.,...]  
                                OPTIONAL  
1  IDENTIFIER  
2  inherits from \setupframedtexts
```

```
\definehead [...1.] [...2.]  
1  IDENTIFIER  
2  SECTION
```

`\defineindenting [.1.] [...,2.,...]`

- 1 IDENTIFIER
- 2 *inherits from* \setupindentations

`\defineinteractionmenu [...,1,...] [...,2.,...] OPTIONAL`

- 1 left right top bottom IDENTIFIER
- 2 *inherits from* \setupinteractionmenu

`\defineinteractionmenu [.1.] [2.] [...,3.,...] OPTIONAL OPTIONAL`

- 1 left right top bottom IDENTIFIER
- 2 left right top bottom IDENTIFIER
- 3 *inherits from* \setupinteractionmenu

`\definelabel [.1.] [...,2.,...]`

- 1 IDENTIFIER
- 2 text = TEXT
location = inmargin intext
way = bytext bycd:section
blockway = yes no
headstyle =
headcolor = IDENTIFIER
before = COMMAND
after = COMMAND

`\definelist [.1.] [2.] [...,3.,...] OPTIONAL OPTIONAL`

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 *inherits from* \setuplist

`\definelogo [...]1 [...]2 [...]3 [...,4.,...] OPTIONAL`

- 1 IDENTIFIER
- 2 top header footer bottom
- 3 none page leftedge leftmargin left middle right rightmargin rightedge
- 4 command = COMMAND TEXT
state = start stop

`\definemakeup [.1.] [...,2.,...]`

- 1 IDENTIFIER
- 2 *inherits from* \setupmakeup

`\definemarking [.1.] [2.] OPTIONAL`

- 1 IDENTIFIER
- 2 IDENTIFIER

`\defineoutput [.1.] [...2,...] OPTIONAL`

- 1 IDENTIFIER
- 2 IDENTIFIER

```
\defineoverlay [...1;...] [...2.]
```

- 1 IDENTIFIER
- 2 COMMAND

```
\definepalet [...1.] [...,2.,...]
```

- 1 IDENTIFIER
- 2 IDENTIFIER = IDENTIFIER

```
\definepapersize [...1.] [...,2.,...]
```

- 1 IDENTIFIER
- 2 width = DIMENSION
- height = DIMENSION
- offset = DIMENSION
- scale = NUMBER

```
\defineparagraphs [...1.] [...,2.,...]
```

- 1 IDENTIFIER
- 2 n = NUMBER
- rule = on off
- height = fit DIMENSION
- before = COMMAND
- after = COMMAND
- inner = COMMAND
- distance = DIMENSION
- tolerance = verystRICT strict tolerant verytolerant stretch
- align =

```
\defineprofile [...1;...] [...2;...]
```

- 1 IDENTIFIER
- 2 IDENTIFIER

```
\defineprogram [...1.] [...2.] [...3.]
```

- 1 IDENTIFIER
- 2 TEXT
- 3 TEXT

```
\definereference [...1.] [...2;...]
```

- 1 IDENTIFIER
- 2 REFERENCE

```
\definereferenceformat [...1.] [...,2.,...]
```

- 1 IDENTIFIER
- 2 left = TEXT
- right = TEXT
- text = TEXT
- label = IDENTIFIER

`\definereferencelist [.1.] [...,.2.,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupreferencelist

`\defineregister [.1.] [.2.]`

- 1 SINGULAR NAME
- 2 PLURAL NAME

`\definesection [.*.]`

- * IDENTIFIER

`\definesectionblock [.1.] [...,.2.,...]`
OPTIONAL

- 1 *inherits from* \setupsectionblock
- 2 *inherits from* \setupsectionblock

`\definesorting [.1.] [.2.] [.3.]`
OPTIONAL

- 1 SINGULAR NAME
- 2 PLURAL NAME
- 3 COMMAND

`\definestartstop [.1.] [...,.2.,...]`

- 1 IDENTIFIER
- 2 before = COMMAND
after = COMMAND
style =
commands = COMMAND

`\definesubfield [.1.] [.2.] [...,3,...]`

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 IDENTIFIER

`\definesymbol [.1.] [.2.]`

- 1 IDENTIFIER
- 2 TEXT

`\definesynonyms [.1.] [.2.] [.3.] [.4.]`
OPTIONAL

- 1 SINGULAR NAME
- 2 PLURAL NAME
- 3 COMMAND
- 4 COMMAND

`\definetabletemplate [.1.] [.2.] [...3.] [...4.]`
OPTIONAL OPTIONAL

1 IDENTIFIER
2 TEXT
3 TEXT
4 TEXT

`\definetabulate [.1.] [...2.] [...3.]`
OPTIONAL OPTIONAL

1 IDENTIFIER
2 IDENTIFIER
3 TEXT

`\definetext [.1.] [...2.] [...3.] [...4.] [...5.]`
OPTIONAL OPTIONAL

1 IDENTIFIER
2 header footer
3 TEXT
4 TEXT
5 TEXT

`\definetype [.1.] [...,2_,...]`

1 IDENTIFIER
2 *inherits from \setuptype*

`\definetyping [.1.] [...,2_,...]`

1 *inherits from \setuptyping*
2 *inherits from \setuptyping*

`\defineversion [.1.] [...,2_,...]`

1 IDENTIFIER
2 NUMBER

`\DESCRIPTION {.1.} .2.`

1 TEXT
2 EMPTY

`\determineheadnumber [...]`

* SECTION

`\determinelistcharacteristics [...,1_,...] [...,2_,...]`
OPTIONAL

1 IDENTIFIER
2 *inherits from \setuplist*

`\disableinteractionmenu [.1.] [...,2...]`

- 1 left right top bottom IDENTIFIER
- 2 REFERENCE

`\emptylines [...]`

- * NUMBER

`\ENUMERATION ...`

- * EMPTY

`\externalfigure [.1.] [...,2...]`
OPTIONAL

- 1 FILE
- 2 *inherits from* \setupexternalfigures

`\field [...]`

- * IDENTIFIER

`\fieldstack [.1.] [...,2...] [...,3...]`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 *inherits from* \setupfields

`\fillinfield [.1.] {.2.}`
OPTIONAL

- 1 TEXT
- 2 TEXT

`\fillinline [...,1...] .2.`
OPTIONAL

- 1 *inherits from* \setupfillinlines
- 2 EMPTY

`\fillinrules [...,1...] {.2.} {.3.}`
OPTIONAL OPTIONAL

- 1 *inherits from* \setupfillinrules
- 2 TEXT
- 3 TEXT

`\fillintext [...,1...] {.2.} {.3.}`
OPTIONAL OPTIONAL

- 1 *inherits from* \setupfillinrules
- 2 TEXT
- 3 TEXT

`\fitfield [...]`

* IDENTIFIER

`\fixedspaces`

`\followprofile {...} [...]`

1 TEXT

2 TEXT

`\followprofileversion {...} [...] [...]`

1 TEXT

2 TEXT

3 IDENTIFIER

`\followversion {...} [...]`

1 TEXT

2 TEXT

`\footnote [...] {...}`
OPTIONAL

1 REFERENCE

2 TEXT

`\footnotetext [...] {...}`
OPTIONAL

1 REFERENCE

2 TEXT

`\forceblocks [...,1...] [...,2...]`
OPTIONAL

1 IDENTIFIER

2 IDENTIFIER

`\fraction {...} {...}`

1 TEXT

2 TEXT

`\framed [...,1,...] {...}`
OPTIONAL

1 *inherits from \setupframed*

2 TEXT

`\FRAMEDTEXT [...,*,...]`
OPTIONAL

* *inherits from \setupframedtexts*

`\from [...]`

* REFERENCE

`\getbuffer [...]`
OPTIONAL

* IDENTIFIER

`\getmarking [...]1 [...]2`

1 IDENTIFIER

2 first last previous both all current

`\godown [...]`

* DIMENSION

`\goto {...}1 {...}2 [...,3...]`

1 TEXT

2 TEXT

3 REFERENCE

`\gotobox {...}1 [...,2...]`

1 TEXT

2 REFERENCE

`\graycolor [...]`

* TEXT

`\grid [...,*...]`

* x = NUMBER
y = NUMBER
nx = NUMBER
ny = NUMBER
dx = NUMBER
dy = NUMBER
xstep = NUMBER
ystep = NUMBER
offset = yes no
factor = NUMBER
scale = NUMBER
unit = cm pt em mm ex es in
location = left middle

`\hairline`

`\head [...,*...]`
OPTIONAL

* REFERENCE

\headnumber [...]
OPTIONAL

* SECTION

\headtext {...}

* TEXT

\hideblocks [...,¹...] [...,²...]
OPTIONAL

1 IDENTIFIER

2 IDENTIFIER

\high {...}

* TEXT

\hl [...]

* NUMBER

\in {...¹} {...²} [...³]

1 TEXT

2 TEXT

3 REFERENCE

\INDENTATION ...

* EMPTY

\indenting [...,*...]

*

\inframed [...,¹...] {...²}
OPTIONAL

1 inherits from \setupframed

2 TEXT

\ininner [...¹] [...²] {...³}
OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

\inleft [...¹] [...²] {...³}
OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inline [...]`

* REFERENCE

`\inmargin [...] [...] {...}`
 OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inotherrmargin [...] [...] {...}`
 OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inouter [...] [...] {...}`
 OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inright [...] [...] {...}`
 OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\installlanguage [...],2...,...`

1 IDENTIFIER

2 spacing = packed broad
 lefthyphenmin = NUMBER
 righthyphenmin = NUMBER
 state = start stop
 leftsentence = COMMAND
 rightsentence = COMMAND
 leftsubsentence = COMMAND
 rightsubsentence = COMMAND
 leftquote = COMMAND
 rightquote = COMMAND
 leftquotation = COMMAND
 rightquotation = COMMAND
 leftspeech = COMMAND
 middlespeech = COMMAND
 rightspeech = COMMAND
 limittext = TEXT
 date = TEXT
 compoundhyphen = COMMAND
 leftcompoundhyphen = COMMAND
 rightcompoundhyphen = COMMAND
 default = IDENTIFIER

`\interactionbar [...],*...,...]`

* *inherits from* \setupinteractionbar

`\interactionbuttons [...,1...] [...2,...]`
OPTIONAL

- 1 *inherits from* \setupinteractionbar
- 2 IDENTIFIER

`\item [...,*...]`
OPTIONAL

- * REFERENCE

`\items [...,1...] {...2...}`
OPTIONAL

- 1 *inherits from* \setupitems
- 2 TEXT

`\its [...,*...]`
OPTIONAL

- * REFERENCE

`\keepblocks [...,1...] [...2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 all IDENTIFIER

`\LABELING [...]`
OPTIONAL

- * REFERENCE

`\labels [...]`

- * IDENTIFIER

`\labeltext {...}`

- * TEXT

`\language [...]`

- *

`\leftaligned {...}`

- * TEXT

`\listsymbol [...1] {...2}`

- 1 IDENTIFIER
- 2 TEXT

`\loadSORTS`

`\loadSYNONYMS`

`\logfields`

`\lohi [.1.] {.2.} {.3.}`
OPTIONAL

- 1 low
- 2 TEXT
- 3 TEXT

`\low {...}`

- * TEXT

`\mainlanguage [...]`

*

`\mar [...1...] {.2.}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\marginrule [.1.] {.2.}`

- 1 NUMBER
- 2 TEXT

`\margintext [.1.] [.2.] {.3.}`
OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\marking [.1.] {.2.}`

- 1 IDENTIFIER
- 2 TEXT

`\markversion`

`\mathematics {...}`

- * TEXT

`\mediaeval {...}`

- * TEXT

`\midaligned {...}`

* TEXT

`\mirror {...}`

* TEXT

`\MONTH {...}`

* TEXT

`\month {...}`

* TEXT

`\moveongrid [...*,...]`
OPTIONAL

* standard top both bottom -top -both -bottom TEXT high middle low page broad fit depth line reset
none DIMENSION

`\name {...}`

* TEXT

`\nextSECTION`

`\nocap {...}`

* TEXT

`\noheaderandfooterlines`

`\noindenting`

`\nolist {...}`

* TEXT

`\nomarking {...}`

* TEXT

`\nomoreblocks`

`\nomorefiles`

`\nop`

`\nospace`

`\note [...]`

* REFERENCE

`\notopandbottomlines`

`\nowhitespace`

`\numbers {...}`

* TEXT

`\overbar {...}`

* TEXT

`\overbars {...}`

* WORD

`\overstrike {...}`

* TEXT

`\overstrikes {...}`

* WORD

`\packed`

`\page [...,*,...]`

* yes makeup no preference bigpreference left right disable last quadruple even odd blank empty reset
start stop

`\pagereference [...]`

* REFERENCE

`\pagetype [...]`

* IDENTIFIER

`\PARAGRAPH`

`\part [...1,...] {..2}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\periods [...]`

- * NUMBER

`\placebookmarks [...1,...] [...2,...]`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER all

`\placecombinedlist [..1] [...2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcombinedlist

`\placeCOMBINEDLIST [..1] [...2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcombinedlist

`\placeFLOAT [..1] [...2,...] {..3} {..4}`
OPTIONAL OPTIONAL

- 1 left right here top bottom inleft inright inmargin margin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge inner outer line high low fit page leftpage rightpage opposite always auto force tall reset line height depth split 90 180 270
- 2 REFERENCE
- 3 TEXT
- 4 TEXT

`\placefootnotes [...*,...]`
OPTIONAL

- * *inherits from* \setupfootnotes

`\placeformula [...1,...] {..2} $$..3$$`
OPTIONAL OPTIONAL

- 1 REFERENCE
- 2 TEXT
- 3

`\placelegend {..1} {..2}`

- 1 TEXT
- 2 TEXT

`\placelist [...1,...] [...2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setuplist

`\placelistofFLOATS`

`\placelistofSORTS`

`\placelistofSYNONYMS`

`\placelocalfootnotes [...,*,...]`
OPTIONAL

* *inherits from* \setupfootnotes

`\placelogos [...,*,...]`
OPTIONAL

* IDENTIFIER

`\placeongrid [.1.] {.2.}`
OPTIONAL

1 *inherits from* \moveongrid

2 TEXT

`\placeontopofeachother {.1.} {.2.}`

1 TEXT

2 TEXT

`\placereferencelist [...,*,...]`

* IDENTIFIER

`\placeregister [.1.] [...,*2,...]`
OPTIONAL

1 IDENTIFIER

2 *inherits from* \setupregister

`\placeREGISTER [...,*,...]`
OPTIONAL

* *inherits from* \setupregister

`\placesidebyside {.1.} {.2.}`

1 TEXT

2 TEXT

`\placesubformula [...,*1,...] {.2.} $$.*3.$$`
OPTIONAL OPTIONAL

1 REFERENCE

2 TEXT

3

`\position (...1,...) {...2}`

1 POSITION

2 TEXT

`\processblocks [...1;...] [...2;...] OPTIONAL`

1 IDENTIFIER

2 IDENTIFIER

`\processpage [...1;...] [...2.]`

1 IDENTIFIER

2 yes no

`\program [...]`

* IDENTIFIER

`\publication [...]`

* REFERENCE

`\quotation {...}`

* TEXT

`\quote {...}`

* TEXT

`\ran {...}`

* TEXT

`\ref [...1.] [...2.]`

1 t p r s e

2 REFERENCE

`\reference [...1.] {...2.}`

1 REFERENCE

2 TEXT

`\referral [...,**,...]`

* bet = TEXT

ken = TEXT

dat = TEXT

van = TEXT

aan = TEXT

ref = TEXT

`\referraldate`

`\REGISTER` [¹._{OPTIONAL}.] {...².+...}

- 1 TEXT
- 2 ENTRY

`\reserveFLOAT` [...¹._{OPTIONAL}.] [²._{OPTIONAL}.] [...³._{OPTIONAL}.] {...⁴.}

- 1 height = DIMENSION
width = DIMENSION
frame = on off
- 2 TEXT
- 3 REFERENCE
- 4 TEXT

`\reset` [...^{*}.]

- * IDENTIFIER

`\resetmarking` [...^{*}.]

- * IDENTIFIER

`\resettextcontent` [...¹.] [...².] [...³._{OPTIONAL}.]

- 1
- 2
- 3 lefttext middletext righttext

`\rightaligned` {...^{*}.}

- * TEXT

`\romannumerals` {...^{*}.}

- * TEXT

`\Romannumerals` {...^{*}.}

- * TEXT

`\rotate` [...¹._{OPTIONAL}.] {...².}

- 1 inherits from \setuprotate
- 2 TEXT

`\scale` [...¹._{OPTIONAL}.] {...².}

- 1 sx = NUMBER
sy = NUMBER
- 2 TEXT

\screen

\section [...,¹...] {..².}
 OPTIONAL

- 1 REFERENCE
- 2 TEXT

\seeREGISTER [...,¹.] {..².} {...+..³+...}
 OPTIONAL

- 1 TEXT
- 2 TEXT
- 3 ENTRY

\selectblocks [...,¹...] [...,²...] [...,³.]
 OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 criterium = all SECTION

\selectpaper [...,*,...]

- * family = 1 2

\selectversion

\settextcontent [...,¹.] [...,².] [...,³.] [...,⁴.] [...,⁵.]
 OPTIONAL OPTIONAL OPTIONAL

- 1
- 2
- 3
- 4
- 5

\setupalign [...,*,...]

- * width left right middle inner outer wide broad height bottom line reset hanging nothanging
 hyphenated nothyphenated lessshyphenation morehyphenation new old normal yes no flushleft flushright
 flushouter flushinner center hz nohz spacing nospacing tolerant verytolerant stretch

\setuparranging [...,*,...]

- * disable 2*16 2*8 2*4 2*2 2**2 2*2*4 2*4*2 2UP 2DOWN 2SIDE 2TOP mirrored rotated doublesided
 negative background 90 180 270

\setupbackground [...,*,...]

- * leftoffset = DIMENSION
- rightoffset = DIMENSION
- topoffset = DIMENSION
- bottomoffset = DIMENSION
- before = COMMAND
- after = COMMAND
- state = start stop
- inherits from \setupframed

```
\setupbackgrounds [1...] [2...] [3...]
                        OPTIONAL      OPTIONAL
1  top header TEXT footer bottom page paper leftpage rightpage
2  leftedge leftmargin TEXT rightmargin rightedge
3  state = start stop cd:repeat
    inherits from \setupframed
```

```
\setupblackrules [...,*,...]
```

```
*  width      = DIMENSION max
   height     = DIMENSION max
   depth      = DIMENSION max
   alternative = a b
   distance   = DIMENSION
   n          = NUMBER
   color      = IDENTIFIER
```

```
\setupblank [*...]
                OPTIONAL
```

```
*  normal default standard line halfline DIMENSION big medium small fixed flexible global unknown
```

```
\setupblock [...,1...] [...,2...,...]
```

```
1  IDENTIFIER
2  before = COMMAND
   after  = COMMAND
   inner  = COMMAND
   style  =
   file   = FILE
```

```
\setupbodyfont [...,*,...]
```

```
*  IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt
... 12pt
```

```
\setupbodyfontenvironment [1...] [2...] [3*,...]
                        OPTIONAL  OPTIONAL      OPTIONAL
```

```
1  inherits from \definebodyfontenvironment
2  inherits from \definebodyfontenvironment
3  inherits from \definebodyfontenvironment
```

```
\setupbottom [1...] [...,2*,...]
                OPTIONAL
```

```
1  inherits from \setupheader
2  inherits from \setupheader
```

```
\setupbottomtexts [1...] [2...] [3...]
                   OPTIONAL  OPTIONAL  OPTIONAL
```

```
1
2
3
```

```
\setupbuffer [1...] [...,2*,...]
                OPTIONAL
```

```
1  IDENTIFIER
2  paragraph = NUMBER
   before    = COMMAND
   after     = COMMAND
```

```
\setupbuttons [...,*,...]
```

```
* state = start stop  
inherits from \setupframed
```

```
\setupcapitals [...,*,...]
```

```
* title = yes no  
sc      = yes no
```

```
\setupcaption [.1.] [...,2,...]
```

```
1 IDENTIFIER  
2 inherits from \setupcaptions
```

```
\setupcaptions [...,*,...]
```

```
* location = top bottom none high low middle left middle right lefthanging righthanging leftmargin  
rightmargin innermargin outermargin  
width      = fit broad max DIMENSION  
minwidth   = fit DIMENSION  
headstyle  =  
style      =  
number     = yes no none  
inbetween  = COMMAND  
align      =  
conversion = numbers characters Characters romannumerals Romannumerals  
way        = bytext bycd:section  
separator  = TEXT  
stopper    = TEXT  
command    = COMMAND  
distance   = DIMENSION
```

```
\setupclipping [...,*,...]
```

```
* state      = start stop  
n            = NUMBER  
nx           = NUMBER  
ny           = NUMBER  
x            = NUMBER  
y            = NUMBER  
sx           = NUMBER  
sy           = NUMBER  
width        = DIMENSION  
height       = DIMENSION  
hoffset      = DIMENSION  
voffset      = DIMENSION  
offset       = DIMENSION  
leftoffset   = DIMENSION  
rightoffset  = DIMENSION  
topoffset    = DIMENSION  
bottomoffset = DIMENSION  
mp           = IDENTIFIER
```

```
\setupcolor [...*...]
```

```
* IDENTIFIER
```

`\setupcolors [...,*=.,...]`

```
*  state      = start stop global local
   conversion = yes no always
   reduction  = yes no
   rgb        = yes no
   cmyk       = yes no
   mpcmyk     = yes no
   mpspot     = yes no
   textcolor  = IDENTIFIER
   split      = c m y k p s no IDENTIFIER
   criterium  = all none
```

`\setupcolumns [...,*=.,...]`

OPTIONAL

```
*  n          = NUMBER
   ntop       = NUMBER
   rule       = on off
   height     = DIMENSION
   tolerance  = verystRICT strict tolerant verytolerant stretch
   distance   = DIMENSION
   balance    = yes no
   align      = text
   blank      = fixed halfline line flexible big medium small
   option     = background
   direction  = left right
   inherits from \setupframed
```

`\setupcombinations [...,*=.,...]`

```
*  before     = COMMAND
   inbetween  = COMMAND
   after      = COMMAND
   distance   = DIMENSION
   height     = DIMENSION fit
   width      = DIMENSION fit
   location   = top middle bottom left right
   align      =
   style      =
   color      = IDENTIFIER
```

`\setupcombinedlist [.1.] [...,2=.,...]`

```
1  IDENTIFIER
2  level = 1 2 3 4 SECTION current
   inherits from \setuplist
```

`\setupcomment [...,*=.,...]`

```
*  state      = start stop
   width      = DIMENSION
   height     = DIMENSION
   color      = IDENTIFIER
   title      = TEXT
   space      = yes no
   symbol     = normal New Balloon Addition Help Paragraph Key IDENTIFIER
   option     = max buffer
   margin     = DIMENSION
   distance   = DIMENSION
```


`\setupdescriptions [...1,...] [...,2.,...]`
OPTIONAL

```
1 IDENTIFIER
2 style      =
  color      = IDENTIFIER
  width      = fit broad DIMENSION
  distance   = DIMENSION
  sample     = TEXT
  text       = TEXT
  closesymbol = TEXT
  closecommand = \...#1
  closesymbol = TEXT
  titleleft  = TEXT
  titleright = TEXT
  titledistance = DIMENSION
  titlestyle =
  titlecolor = IDENTIFIER
  align      =
  margin     = standard yes no DIMENSION
  location   = left right top serried inmargin inleft inright hanging
  headstyle  =
  headcolor  = IDENTIFIER
  headcommand = COMMAND
  hang       = fit broad NUMBER
  before     = COMMAND
  inbetween  = COMMAND
  after      = COMMAND
  indentnext =
  indenting  =
  command    = COMMAND
```

`\setupenumerations [...1,...] [...,2.,...]`
OPTIONAL

```
1 IDENTIFIER
2 inherits from \setupdescriptions
```

`\setuexternalfigures [.*.]`

```
* scale      = NUMBER
  yscale     = NUMBER
  yscale     = NUMBER
  factor     = max fit broad
  wfactor    = NUMBER max broad fit
  hfactor    = NUMBER max broad fit
  width      = DIMENSION
  height     = DIMENSION
  frame      = on off
  preset     = yes no
  display    = FILE
  preview    = yes no
  repeat     = yes no
  object     = yes no
  type       = eps mps pdf tif png jpg mov cd:tex
  method     = eps mps pdf tif png jpg mov cd:tex
  option     = frame empty test
  frames     = on off
  ymax       = NUMBER
  xmax       = NUMBER
  directory  = TEXT
  location   = local global default none
  maxwidth   = DIMENSION
  maxheight  = DIMENSION
  conversion = TEXT
  prefix     = TEXT
```

```
\setupfield [.1.] [...,2...] [...,3...] [...,4...] [...,5...]
```

```
1 IDENTIFIER
2 label horizontal vertical frame
3 inherits from \setupfields
4 see 4
5 see 5
```

```
\setupfields [...,1...] [...,2...] [...,3...] [...,4...]
```

```
1 reset label horizontal vertical frame
2 n = NUMBER
  distance = DIMENSION
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  color = IDENTIFIER
  style =
  align =
  option = readonly required protected sorted unavailable hidden printable
  clickin = REFERENCE
  clickout = REFERENCE
  regionin = REFERENCE
  regionout = REFERENCE
  afterkey = REFERENCE
  format = REFERENCE
  validate = REFERENCE
  calculate = REFERENCE
  fieldoffset = DIMENSION
  fieldframecolor = IDENTIFIER
  fieldbackgroundcolor = IDENTIFIER
  inherits from \setupframed
3 inherits from \setupfields
4 inherits from \setupfields
```

```
\setupfillinlines [...,*...]
```

```
* width = DIMENSION
  margin = DIMENSION
  distance = DIMENSION
  before = COMMAND
  after = COMMAND
```

```
\setupfillinrules [...,*...]
```

```
* width = fit broad DIMENSION
  distance = DIMENSION
  before = COMMAND
  after = COMMAND
  style =
  n = NUMBER
  interlinespace = small medium big
  separator = TEXT
```

```
\setupfloat [.1.] [...,2...]
```

```
1 IDENTIFIER
2 height = DIMENSION
  width = DIMENSION
  maxheight = DIMENSION
  maxwidth = DIMENSION
  minwidth = DIMENSION
  default = IDENTIFIER
  pageboundaries = LIST
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  location = left middle right
  inherits from \setupframed
```

`\setupfloats [...,*,...]`

```
*   location           = left right middle
    width              = fit DIMENSION
    before             = COMMAND
    after              = COMMAND
    margin             = DIMENSION
    spacebefore        = small medium big none
    spaceafter         = small medium big none
    sidespacebefore    = small medium big none
    sidespaceafter     = small medium big none
    indentnext         =
    ntop               = NUMBER
    nbottom            = NUMBER
    nlines             = NUMBER
    default            = IDENTIFIER
    tolerance          = 0 1 2
    leftmargindistance = DIMENSION
    rightmargindistance = DIMENSION
    sidealign          = normal line
    numbering          = yes nocheck
    inherits from \setupframed
```

`\setupfloatsplitting [...,*,...]`

```
*   conversion = numbers characters Characters romannumerals Romannumerals
    lines      = NUMBER
```

`\setupfooter [1.] [...,2.,...]`
OPTIONAL

```
1   inherits from \setupheader
2   inherits from \setupheader
```

`\setupfootertexts [1.] [2.] [3.]`
OPTIONAL OPTIONAL OPTIONAL

```
1
2
3
```

`\setupfootnotedefinition [...,*,...]`

```
*   inherits from \setupdescriptions
```

`\setupfootnotes [...,*,...]`

```
*   conversion      = numbers characters Characters romannumerals Romannumerals
    way             = bytext bycd:section
    location        = page TEXT columns firstcolumn lastcolumn high none
    rule           = on off
    before         = COMMAND
    after          = COMMAND
    width          = DIMENSION
    height         = DIMENSION
    bodyfont       =
    style          =
    distance       = DIMENSION
    columndistance = DIMENSION
    margindistance = DIMENSION
    n              = NUMBER
    numbercommand  = \...#1
    textcommand    = \...#1
    split         = tolerant strict verystrict NUMBER
    textstyle      =
    textcolor      = IDENTIFIER
    interaction    = yes no
    factor         = NUMBER
    inherits from \setupframed
```

```
\setupforms [...,*,...]
```

```
* method = HTML FDF
```

```
\setupformulae [...,*,...]
```

```
* location      = left right
left            = TEXT
right           = TEXT
align           =
option          = middle
strut           = yes no
distance        = DIMENSION
margin          = DIMENSION standard yes no
align           = flushleft flushright middle center
leftmargin      = DIMENSION
rightmargin     = DIMENSION
indentnext     =
alternative     = IDENTIFIER
spacebefore     = DIMENSION
after           = DIMENSION
separator       = TEXT
conversion      = numbers characters Characters romannumerals Romannumerals TEXT
```

```
\setupframed [1...] [2*,*,...]
```

OPTIONAL

```
1 IDENTIFIER
2 height        = fit broad DIMENSION
width           = fit broad fixed local DIMENSION
autowidth       = yes no force
offset          = none overlay default DIMENSION
location        = depth hanging high lohi low top middle bottom keep
option          = none empty
strut           = yes no global local
align           =
bottom          = COMMAND
top             = COMMAND
frame           = on off none overlay
topframe        = on off
bottomframe     = on off
leftframe       = on off
rightframe      = on off
frameoffset     = DIMENSION
framedepth      = DIMENSION
framecorner     = round rectangular
frameradius     = DIMENSION
framecolor      = IDENTIFIER
background      = screen color none foreground IDENTIFIER
backgroundscreen = NUMBER
backgroundcolor = IDENTIFIER
backgroundoffset = frame DIMENSION
backgrounddepth = DIMENSION
backgroundcorner = round rectangular
backgroundradius = DIMENSION
depth           = DIMENSION
corner          = round rectangular
radius          = DIMENSION
empty           = yes no
foregroundcolor = IDENTIFIER
foregroundstyle =
rulethickness   = DIMENSION
```

`\setupframedtexts [...]1 [...]2,...]`

OPTIONAL

```
1 IDENTIFIER
2 bodyfont      =
  style         =
  left          = COMMAND
  right         = COMMAND
  before        = COMMAND
  after         = COMMAND
  inner         = COMMAND
  linecorrection = on off
  depthcorrection = on off
  margin        = standard yes no
  location      = left right middle none
  indenting     =
  inherits from \setupframed
```

`\setuphead [...]1,...]` `[...]2,...]`

```
1 SECTION
2 style          =
  textstyle      =
  numberstyle    =
  color          = IDENTIFIER
  textcolor      = IDENTIFIER
  numbercolor    = IDENTIFIER
  number         = yes no
  ownnumber      = yes no
  page           = left right yes
  continue       = yes no
  header         = none empty high nomarking
  text           = none empty high nomarking
  footer         = none empty high nomarking
  before         = COMMAND
  inbetween      = COMMAND
  after          = COMMAND
  alternative    = normal inmargin middle TEXT
  hang           = none broad fit line NUMBER
  command        = \...#1#2
  numbercommand  = \...#1
  textcommand    = \...#1
  deepnumbercommand = \...#1
  deeptextcommand = \...#1
  prefix         = + - TEXT
  placehead      = yes no empty
  incrementnumber = yes no LIST FILE
  resetnumber    = yes no
  file           = IDENTIFIER
  expansion      = yes no command
  margintext     = yes no
  inherits from \setupheads
```

`\setupheader [...]1] [...]2,...]`

OPTIONAL

```
1 TEXT margin edge
2 state          = normal stop start empty high none nomarking IDENTIFIER
  strut         = yes no
  style         =
  leftstyle      =
  rightstyle     =
  leftwidth      = DIMENSION
  rightwidth     = DIMENSION
  before         = COMMAND
  after          = COMMAND
```

`\setupheadertexts [...]1] [...]2] [...]3]`

OPTIONAL OPTIONAL OPTIONAL

```
1
2
3
```

`\setupheadnumber [.1.] [.2.]`

1 SECTION
2 NUMBER +cd:number -cd:number

`\setupheads [...,.*.,...]`

* sectionnumber = yes NUMBER no
alternative = normal margin middle TEXT paragraph
separator = TEXT
stopper = TEXT
align =
aligntitle = yes float no
tolerance = verystRICT strict tolerant verytolerant stretch
indentnext =
command = \...#1#2
margin = DIMENSION

`\setupheadtext [.1.] [.2.]`
OPTIONAL

1
2 IDENTIFIER = TEXT

`\setuphyphenmark [.*.]`

* sign = -- --- - ~ () = /

`\setupindentations [...,1...] [...,2...]`
OPTIONAL

1 IDENTIFIER
2 style =
headstyle =
width = fit DIMENSION
text = TEXT
sample = TEXT
before = COMMAND
after = COMMAND
distance = DIMENSION
separator = TEXT

`\setupindenting [...,*...]`

*

`\setupinmargin [.1.] [...,2...]`
OPTIONAL

1 left right NUMBER
2 location = left right both
style =
before = COMMAND
after = COMMAND
align =
line = NUMBER
distance = DIMENSION
separator = TEXT
width = DIMENSION
distance = DIMENSION
stack = yes no
inherits from \setupframed

`\setupinteraction [...,*,...]`

```
* state      = start stop
menu         = on off
page         = yes no
click        = yes no
split        = yes no
display      = new
openaction   = REFERENCE
closeaction  = REFERENCE
openpageaction = REFERENCE
closepageaction = REFERENCE
calculate    = IDENTIFIER
strut        = yes no
width        = DIMENSION
height       = DIMENSION
depth        = DIMENSION
style        =
color        = IDENTIFIER
contrastcolor = IDENTIFIER
symbolset    = IDENTIFIER
title        = TEXT
subtitle     = TEXT
author       = TEXT
date         = TEXT
keyword      = TEXT
fieldlayer   = auto IDENTIFIER
```

`\setupinteractionbar [...,*,...]`

```
* state      = start stop
alternative  = a b c d e f g
symbol       = yes no
width        = DIMENSION height fit
height       = DIMENSION height fit
depth        = DIMENSION
color        = IDENTIFIER
step         = NUMBER small medium big
inherits from \setupframed
```

`\setupinteractionmenu [...,1...] [...,2,...]`

```
1 IDENTIFIER
2 before      = COMMAND
after         = COMMAND
inbetween     = COMMAND
left          = COMMAND
right         = COMMAND
middle        = COMMAND
state         = start stop none local
style         =
color         = IDENTIFIER
contrastcolor = IDENTIFIER
distance      = overlay DIMENSION
samepage      = yes empty no none
unknownreference = yes empty no none
leftoffset    = DIMENSION
rightoffset   = DIMENSION
topoffset     = DIMENSION
bottomoffset  = DIMENSION
position      = yes no
inherits from \setupframed
```

`\setupinteractionscreen [...,*,...]`

```
* width      = DIMENSION fit max
height       = DIMENSION fit max
backspace    = DIMENSION
topspace     = DIMENSION
horoffset    = DIMENSION
veroffset    = DIMENSION
option       = max fit doublesided bookmark
delay        = NUMBER none
```

`\setupinterlinespace [...]`

OPTIONAL

* reset small medium auto big on off

`\setupinterlinespace [...,.*,...]`

* height = NUMBER
depth = NUMBER
line = DIMENSION
top = NUMBER
bottom = NUMBER

`\setupitemgroup [...]1 [...]2 [...,3...] [...,4*,...]`

OPTIONAL

OPTIONAL

OPTIONAL

1 IDENTIFIER
2 NUMBER each
3 standard broad serried packed unpacked nowhite before after stopper joinedup atmargin inmargin
autointro loose repeat SECTION paragraph intext random reverse
4 margin = no standard DIMENSION
leftmargin = no standard DIMENSION
rightmargin = no standard DIMENSION
width = DIMENSION
distance = DIMENSION
factor = NUMBER
items = NUMBER
start = NUMBER
before = COMMAND
inbetween = COMMAND
after = COMMAND
left = TEXT
right = TEXT
beforehead = COMMAND
afterhead = COMMAND
headstyle =
marstyle =
symstyle =
stopper = TEXT
n = NUMBER
symbol = NUMBER
align =
symalign =
indentnext =

`\setupitems [...,.*,...]`

* location = left right inmargin top bottom
symbol = 1 2 ... n a ... TEXT none
width = DIMENSION
n = NUMBER unknown
before = COMMAND
inbetween = COMMAND
align =
after = COMMAND

`\setuplabeltext [...]1 [...]2`

OPTIONAL

1
2 IDENTIFIER = TEXT

`\setuplanguage [...]1 [...,2*,...]`

1
2 *inherits from* \installlanguage

`\setuplayout [...,*.,...]`

```
*   width           = DIMENSION   fit   middle
    height          = DIMENSION   fit   middle
    backspace       = DIMENSION
    topspace        = DIMENSION
    margin           = DIMENSION
    leftmargin       = DIMENSION
    rightmargin      = DIMENSION
    header           = DIMENSION
    footer           = DIMENSION
    top              = DIMENSION
    bottom           = DIMENSION
    leftedge         = DIMENSION
    rightedge        = DIMENSION
    headerdistance   = DIMENSION
    footerdistance   = DIMENSION
    topdistance      = DIMENSION
    bottomdistance   = DIMENSION
    leftmargindistance = DIMENSION
    rightmargindistance = DIMENSION
    leftedgedistance = DIMENSION
    rightedgedistance = DIMENSION
    horoffset        = DIMENSION
    veroffset        = DIMENSION
    style            =
    color            = IDENTIFIER
    marking          = on off color screen TEXT
    location          = left middle right bottom top singlesided doublesided
    scale            = DIMENSION
    nx               = NUMBER
    ny               = NUMBER
    dx               = DIMENSION
    dy               = DIMENSION
    lines            = NUMBER
    columns           = NUMBER
    columndistance    = DIMENSION
    grid             = yes no
    bottomspace       = DIMENSION
    cutspace         = DIMENSION
    textdistance      = DIMENSION
    textwidth        = NUMBER
    textmargin        = DIMENSION
    clipoffset        = DIMENSION
    page             = IDENTIFIER
    paper            = IDENTIFIER
```

`\setuplegend [...,*.,...]`

```
*   n               = NUMBER
    distance         = DIMENSION
    inbetween        = COMMAND
    width            = DIMENSION
    height           = DIMENSION
    location          = right bottom
    bodyfont         =
```

`\setuplinenumbering [...,*.,...]`

```
*   conversion       = numbers characters Characters romannumerals Romannumerals TEXT
    start             = NUMBER
    step              = NUMBER
    width             = DIMENSION
    location           = intext inmargin
    style             =
    prefix            = TEXT
    referencing        = on off
```

`\setuplines [...,.*,...]`

```
* before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  indenting   =
  space       = yes no
```

`\setuplinewidth [...]`

```
* DIMENSION
```

`\setuplist [...,1...] [...,2,...]`

```
1 IDENTIFIER
2 state      = start stop
  alternative = a b c ... none command
  coupling    = on off
  criterium   = SECTION local previous current all
  pageboundaries = LIST
  style       =
  numberstyle =
  textstyle   =
  pagestyle   =
  color       = IDENTIFIER
  command     = \...#1#2#3
  numbercommand = \...#1
  textcommand  = \...#1
  pagecommand  = \...#1
  interaction  = cd:sectionnumber TEXT pagenumber all
  before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  left        = TEXT
  right       = TEXT
  label       = yes no
  prefix      = yes no none
  pagenumber  = yes no
  headnumber  = yes no
  cd:sectionnumber = yes no
  aligntitle  = yes no
  margin      = DIMENSION
  width       = DIMENSION fit
  height      = DIMENSION fit broad
  depth       = DIMENSION fit broad
  distance    = DIMENSION
  separator   = TEXT
  stopper     = TEXT
  symbol      = none 1 2 3 ...
  expansion   = yes no command
  maxwidth    = DIMENSION
inherits from \setupframed
```

`\setuplistalternative [.1.] [...,2,...]`

```
1 a b c
2 command = COMMAND
  width   = DIMENSION
  stretch = DIMENSION
  distance = DIMENSION
```

`\setupmakeup [1.] [2.,.,.]`

```
1 IDENTIFIER
2 width      = DIMENSION
  height     = DIMENSION
  voffset    = DIMENSION
  hoffset    = DIMENSION
  page       = left yes right
  commands   = COMMAND
  doublesided = yes no empty
  headerstate = normal stop start empty none nomarking
  footerstate = normal stop start empty none nomarking
  textstate   = normal stop start empty none nomarking
  topstate    = stop start
  bottomstate = stop start
  pagestate   = stop start
  color       = IDENTIFIER
```

`\setupmarginblocks [.,.*.,.]`

```
* location = inmargin left middle right
  style    =
  width    = DIMENSION
  align    =
  top      = COMMAND
  inbetween = COMMAND
  bottom   = COMMAND
  left     = COMMAND
  right    = COMMAND
  before   = COMMAND
  after    = COMMAND
```

`\setupmarginrules [.*.]`

```
* level      = NUMBER
  rulethickness = DIMENSION
```

`\setupmarking [1.] [2.,.]`

```
1 IDENTIFIER
2 state      = start stop
  separator   = COMMAND
  expansion   = yes no
```

`\setupnarrower [.,.*.,.]`

```
* left      = DIMENSION
  right     = DIMENSION
  middle    = DIMENSION
```

`\setupnumbering [.,.*.,.]`

```
* way      = bytext bycd:section
  state     = start stop
```

`\setupoppositeplacing [.*.]`

```
* state     = start stop
  before    = COMMAND
  inbetween = COMMAND
  after     = COMMAND
```

```
\setupoutput [...,*,...]
```

```
* IDENTIFIER
```

```
\setuppagenumber [...,*,...]
```

```
* number = NUMBER  
state = start stop keep
```

```
\setuppagenumbering [...,*,...]
```

```
* alternative = singlesided doublesided  
location = header footer left right middle margin marginedge inleft inright  
conversion = numbers characters Characters romannumerals Romannumerals  
style =  
left = TEXT  
right = TEXT  
way = bytext bycd:section  
text = TEXT  
numberseparator = TEXT  
textseparator = TEXT  
cd:sectionnumber = yes no  
separator = TEXT  
strut = yes no  
state = start stop  
width = DIMENSION  
command = \...#1
```

```
\setuppagetransitions [...,*,...]
```

OPTIONAL

```
* reset NUMBER
```

```
\setuppalet [...*...]
```

```
* IDENTIFIER
```

```
\setuppaper [...,*,...]
```

```
* paper = IDENTIFIER  
page = IDENTIFIER  
nx = NUMBER  
ny = NUMBER  
width = DIMENSION  
height = DIMENSION  
topspace = DIMENSION  
backspace = DIMENSION  
option = max fit
```

```
\setuppapersize [...1,...] [...2,...]
```

OPTIONAL

```
1 A3 A4 A5 A6 letter ... CD IDENTIFIER landscape mirrored rotated 90 180 270  
2 negative inherits from \setuppapersize
```

```
\setupparagraphnumbering [...,*,...]
```

```
* state = start stop reset line  
style =  
distance = DIMENSION
```

```
\setupparagraphs [1.] [2.] [3.,3.,...]  
                                OPTIONAL
```

```
1 IDENTIFIER  
2 NUMBER each  
3 style      =  
width       = DIMENSION  
height      = DIMENSION  
align       =  
tolerance   = verystRICT STRICT tolerant verytolerant stretch  
distance    = DIMENSION  
before      = COMMAND  
after       = COMMAND  
inner       = COMMAND  
command     = COMMAND  
rule        = on off
```

```
\setuppositioning [3.,3.,...]
```

```
* state      = start overlay  
unit         = cm pt em mm ex es in  
factor       = NUMBER  
scale        = NUMBER  
offset       = yes no  
xstep        = absolute relative  
ystep        = absolute relative
```

```
\setupprofiles [3.,3.,...]
```

```
* option     = test
```

```
\setupprograms [3.,3.,...]
```

```
* directory  = TEXT
```

```
\setuppuplications [3.,3.,...]
```

```
* alternative = apa normal  
inherits from \setupenumerations
```

```
\setupquote [3.,3.,...]
```

```
* before     = COMMAND  
after        = COMMAND  
style        =  
color        = IDENTIFIER  
location     = TEXT margin
```

```
\setupreferencelist [1.] [2.,2.,...]  
                                OPTIONAL
```

```
1 IDENTIFIER  
2 state      = start stop  
criterium    = SECTION local previous all  
command      = COMMAND  
before       = COMMAND  
after        = COMMAND
```

`\setupreferencing [...,.*,...]`

```
* state = start stop
cd:sectionnumber = yes no
prefix = + - TEXT
interaction = label TEXT all symbol
width = DIMENSION
left = COMMAND
right = COMMAND
convertfile = yes no small big
separator = TEXT
autofile = yes no page
global = yes no
```

`\setupregister [.1.] [.2.] [...,3,...]`
OPTIONAL

```
1 SINGULAR NAME
2 IDENTIFIER
3 n = NUMBER
balance = yes no
align =
style =
pagestyle =
textstyle =
indicator = yes no
coupling = yes no
cd:sectionnumber = yes no
criterium = SECTION local all
distance = DIMENSION
symbol = 1 2 ... n a ... none
interaction = page number TEXT
expansion = yes no command
referencing = on off
command = \...#1
location = left middle right
maxwidth = DIMENSION
unknownreference = empty none
alternative = a b A B
prefix = both first none
compress = no yes
deeptextcommand = \...#1
```

`\setuprotate [...,.*,...]`

```
* rotation = NUMBER
location = normal high fit broad depth
inherits from \setupframed
```

`\setupscreens [...,.*,...]`

```
* method = dot rule external
resolution = NUMBER
factor = NUMBER
screen = NUMBER
```

`\setupsection [.1.] [.2.] [...,3,...]`
OPTIONAL

```
1 IDENTIFIER
2 IDENTIFIER
3 conversion = numbers characters Characters romannumerals Romannumerals
previousnumber = yes no
```

`\setupsectionblock [.1.] [...,.2.,...]`

```
1 IDENTIFIER
2 number = yes no
  page   = yes right
  before = COMMAND
  after  = COMMAND
```

`\setupsorting [.1.] [...,.2.,...]`

```
1 IDENTIFIER
2 before = COMMAND
  after  = COMMAND
  command = \...#1
  state   = start stop
  criterium = all used
  style   =
  expansion = yes no command
```

`\setupspacing [...]`

```
* broad packed
```

`\setupstrut [...]`

```
* yes no cap TEXT
```

`\setupsubpagenumber [...,.*.,...]`

```
* way = bytext bycd:section
  state = start stop none
```

`\setupsymbolset [...]`

```
* IDENTIFIER
```

`\setupsynchronization [...,.*.,...]`

```
* state = start stop
```

`\setupsynchronizationbar [...,.*.,...]`

```
* alternative = page local
  width       = DIMENSION height fit
  height      = DIMENSION
  style       =
  color       = IDENTIFIER
  inherits from \setupframed
```

`\setupsynonyms [.1.] [...,.2.,...]`

```
1 IDENTIFIER
2 textstyle =
  synonymstyle =
  location     = left right top serried inmargin inleft inright
  width       = DIMENSION
  state       = start stop
  criterium   = all used
  conversion  = yes no
  expansion   = yes no command
  command     = \...#1#2#3
```

`\setupsystem [...,*,...]`

```
* resolution = NUMBER
file         = TEXT
directory    = TEXT
random       = normal small medium big NUMBER
```

`\setuptab [...,*,...]`

```
* sample     = TEXT
width        = DIMENSION
headstyle    =
location     = left right
```

`\setuptables [...,*,...]`

```
* distance      = small medium big
bodyfont        =
HL              = NUMBER small medium big none
VL              = NUMBER small medium big none
depth           = NUMBER strut
height          = NUMBER strut
rulethickness    = DIMENSION
rulecolor       = IDENTIFIER
align           =
commands        = COMMAND
align           =
background      = screen color none
backgroundscreen = NUMBER
backgroundcolor  = IDENTIFIER
bodyfont        =
```

`\setuptabulate [1.] [2...OPTIONAL]`

```
1 IDENTIFIER
2 unit          = DIMENSION
indenting       =
before          = COMMAND
after           = COMMAND
inner           = COMMAND
EQ              = TEXT
rulecolor       = IDENTIFIER
align           =
rulethickness    = DIMENSION
distance        = blank grid depth DIMENSION small medium big none
bodyfont        =
rule            = normal line
split           = yes no
```

`\setuptext [1.] [2...OPTIONAL]`

```
1 inherits from \setupheader
2 inherits from \setupheader
```

`\setuptextrules [...,*,...]`

```
* location      = left inmargin
before          = COMMAND
after           = COMMAND
inbetween       = COMMAND
width           = DIMENSION
distance        = DIMENSION
bodyfont        =
color           = IDENTIFIER
style           =
rulecolor       = IDENTIFIER
```



```
\setuptexttexts [.1.] [.2.] [.3.]
                  OPTIONAL  OPTIONAL  OPTIONAL
```

1
2
3

```
\setupthinrules [.*.]
```

```
*   interlinespace = small medium big
    n              = NUMBER
    before         = COMMAND
    inbetween      = COMMAND
    after          = COMMAND
    color           = IDENTIFIER
    backgroundcolor = IDENTIFIER
    height         = DIMENSION max
    depth          = DIMENSION max
    alternative     = a b c d
    rulethickness  = DIMENSION
    color           = IDENTIFIER
    background     = color
    backgroundcolor = IDENTIFIER
```

```
\setuptolerance [...,*,...]
```

```
*   horizontal vertical stretch space verystrict strict tolerant verytolerant
```

```
\setuptop [.1.] [...,.2.,...]
          OPTIONAL
```

1 *inherits from* \setupheader
2 *inherits from* \setupheader

```
\setuptoptexts [.1.] [.2.] [.3.]
                OPTIONAL  OPTIONAL  OPTIONAL
```

1
2
3

```
\setuptype [...,*.,...]
```

```
*   space = on off
    option = slanted normal none
    style  =
    color  = IDENTIFIER
```

`\setuptyping` [¹...] [²...,2...,...]
OPTIONAL

```
1 file typing IDENTIFIER
2 space      = on off
  page       = yes no
  option     = slanted normal commands color none
  text       = yes no
  icommand   = COMMAND
  vcommand   = COMMAND
  ccommand   = COMMAND
  before     = COMMAND
  after      = COMMAND
  margin     = DIMENSION standard yes no
  evenmargin = DIMENSION
  oddmargin  = DIMENSION
  blank      = DIMENSION small medium big standard halflines line
  escape     =
  space      = on off
  tab        = NUMBER yes no
  page       = yes no
  indentnext =
  style      =
  color      = IDENTIFIER
  palet      = IDENTIFIER
  lines      = yes no hyphenated
  empty      = yes all no
  numbering  = line file no
  bodyfont   =
```

`\setupunderbar` [^{*}...,*...,...]

```
* alternative = a b c
  rulethickness = DIMENSION
  bottomoffset  = DIMENSION
  topoffset     = DIMENSION
  rulecolor     = IDENTIFIER
```

`\setupurl` [^{*}...,*...,...]

```
* style =
  urlalternative = none both before after
  urlspace      = yes no
```

`\setupversions` [^{*}...,*...,...]

```
* number = NUMBER
  style   =
```

`\setupwhitespace` [^{*}...]
OPTIONAL

```
* none small medium big line fixed fix DIMENSION
```

`\showbodyfont` [^{*}...,*...,...]
OPTIONAL

```
* inherits from \setupbodyfont
```

`\showbodyfontenvironment` [^{*}...,*...,...]
OPTIONAL

```
* inherits from \setupbodyfont
```

`\showcolor` [^{*}...]

```
* IDENTIFIER
```

```
\showcolorgroup [...1.] [...2,...]
```

```
1 IDENTIFIER
2 horizontal vertical name value NUMBER
```

```
\showexternalfigures [...,*,...]  
                                OPTIONAL
```

```
* alternative = a b c
```

```
\showfields [...,*,...]  
                OPTIONAL
```

```
* IDENTIFIER
```

```
\showframe [...]  
            OPTIONAL
```

```
* TEXT margin edge
```

```
\showgrid [...,1,...] {...2.}  
                OPTIONAL
```

```
1 reset top bottom none all lines frame nonumber right left
2 TEXT
```

```
\showlayout
```

```
\showmakeup
```

```
\showpalet [...1.] [...2,...]
```

```
1 IDENTIFIER
2 horizontal vertical name value
```

```
\showprint [...,1,...] [...,2,...] [...,3.,...]
```

```
1 inherits from \setuppapersize
2 inherits from \setuppapersize
3 inherits from \setuplayout
```

```
\showsetups
```

```
\showstruts
```

```
\showsymbolset [...]
```

```
* IDENTIFIER
```

```
\someline [...]
```

```
* REFERENCE
```

`\somewhere {1...} {2...} [3...]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\SORT [1...] {2...}`

- 1 TEXT
- 2 TEXT

`\space`

`\splitfloat [...,1...,...] {2...} {3...}`
OPTIONAL

- 1 *inherits from* \setupfloatsplitting
- 2 TEXT
- 3 TEXT

`\startalignment [...,*...] ... \stopalignment`
OPTIONAL

- * *inherits from* \setupalign

`\startbackground {...} ... \stopbackground`

- * TEXT

`\startBUFFER [...] ... \stopBUFFER`
OPTIONAL

- * IDENTIFIER

`\startbuffer [...] ... \stopbuffer`
OPTIONAL

- * IDENTIFIER

`\startcolor [...] ... \stopcolor`

- * IDENTIFIER

`\startcolumns [...,*...] ... \stopcolumns`
OPTIONAL

- * *inherits from* \setupcolumns

`\startcombination [...] ... \stopcombination`

- * N*M

`\startcomment [1...] [...,2...,...] ... \stopcomment`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcomment

`\startcomponent ... \stopcomponent`

`*`

`\startDESCRIPTION {...} ... \stopDESCRIPTION`

`* TEXT`

`\startdocument [...] ... \stopdocument`

`* IDENTIFIER`

`\startENUMERATION`

`\startenvironment ... \stopenvironment`

`*`

`\startfact .1 .2 .3 ... \stopfact`

`1 EMPTY`

`2 EMPTY`

`3 EMPTY`

`\startfigure [...]1 [...]2 [...,3,...] ... \stopfigure`

`1 IDENTIFIER`

`2 FILE`

`3 factor = NUMBER
frame = on off`

`\startFLOATtext [...]1 [...]2 {...}3 {...}4 ... \stopFLOATtext`
OPTIONAL OPTIONAL

`1 left right high middle low offset tall`

`2 REFERENCE`

`3 TEXT`

`4 TEXT`

`\startFORMULA`

`\startFRAMEDTEXT [...]1 [...,2,...] ... \stopFRAMEDTEXT`
OPTIONAL OPTIONAL

`1 left right middle none`

`2 inherits from \setupframedtexts`

`\starthiding`

`\startinteractionmenu [...] ... \stopinteractionmenu`

`* IDENTIFIER`

```
3 inherits from \setupitemgroup
```

4 EMPTY

* REFERENCE

\startlinecorrection

```
* continue
```

\startlines

\startlocal

\startlocalenvironment

\startlocalfootnotes

```
2 inherits from \setupmakeup
```

\startmarginblock

* NUMBER

\startNAMEmakeup

```
*   left  middle  right
```

`\startopposite`

`\startoverlay {1.} {2.} ... \stopoverlay`

1 TEXT

2 TEXT

`\startoverview [...*,...] ... \stopoverview`

* IDENTIFIER

`\startpacked [...]OPTIONAL ... \stoppacked`

* blank

`\startPARAGRAPH`

`\startpositioning`

`\startpostponing`

`\startproduct ... \stopproduct`

*

`\startprofile [...*,...] ... \stopprofile`

* IDENTIFIER

`\startproject ... \stopproject`

*

`\startquotation [...*,...] ... \stopquotation`

* left middle right

`\startREGISTER [...1.] {...+2.+...}OPTIONAL`

1 TEXT

2 ENTRY

`\startsymbolset [...] ... \stopsymbolset`

* IDENTIFIER

`\startsynchronization`

`\starttable [...] ... \stoptable`

* TEXT IDENTIFIER

`\starttables [...] ... \stoptables`

* TEXT IDENTIFIER

`\startTABULATE [...]1 [...,...,...]2 ... \stopTABULATE`
 OPTIONAL OPTIONAL

1 TEXT

2 *inherits from* \setupexternalfigures

`\starttextrule [...]1 {...}2 ... \stoptextrule`
 OPTIONAL OPTIONAL

1 top bottom

2 TEXT

`\startTYPING`

`\startunpacked`

`\startversion [...,*,...] ... \stopversion`

* NUMBER

`\stretched {...}`

* WORD

`\sub [...,1*,...]`
 OPTIONAL

* REFERENCE

`\subject [...,1*,...]2 {...}`
 OPTIONAL

1 REFERENCE

2 TEXT

`\subsection [...,1*,...]2 {...}`
 OPTIONAL

1 REFERENCE

2 TEXT

`\subsubject [...,1*,...]2 {...}`
 OPTIONAL

1 REFERENCE

2 TEXT

`\subsubsection [...1,...] {..2}`
OPTIONAL

`\subsubsubject [...1,...] {.2.}`
OPTIONAL

`\switchtobodyfont [...,*,...]`

 $\backslash\mathrm{sym}\ \{.\!.\!.\}$

`\symbol` `[.1.]` `[.2.]`
OPTIONAL OPTIONAL

$$\backslash\text{synchronizationbar} \left[\overset{1}{.} \right] \left[\dots, \overset{2}{.}, \dots \right]$$

\synchronize

```
\tab {...} ..
```

`\tex {.*.}`

$$\text{\texttt{\textbackslash textreference}} \left[\text{\texttt{.}}^1 \text{\texttt{.}} \right] \left\{ \text{\texttt{.}}^2 \text{\texttt{.}} \right\}$$

```
\textrule [...]1 {...}2
           OPTIONAL  OPTIONAL
```

- 1 top bottom
- 2 TEXT

```
\thinrule
```

```
\thinrules [...]*
           OPTIONAL
```

- * inherits from \setupthinrules

```
\title [...]1,...2 {...}
           OPTIONAL
```

- 1 REFERENCE
- 2 TEXT

```
\tooltip [...]1 {...}2 {...}3
           OPTIONAL
```

- 1 left right middle
- 2 TEXT
- 3 TEXT

```
\translate [...]*,...]
```

- * IDENTIFIER = TEXT

```
\typ {...}
```

- * TEXT

```
\type {...}
```

- * TEXT

```
\typebuffer [...]
```

- * IDENTIFIER

```
\typefile [...]1 {...}2
           OPTIONAL
```

- 1 IDENTIFIER
- 2 TEXT

```
\underbar {...}
```

- * TEXT

```
\underbars {...}*... ..}
```

- * WORD

\useblocks [...,¹...] [...,²...]
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

\usecommands {...}

- * TEXT

\usedirectory [...,*...]

- * IDENTIFIER reset

\useencoding [...,*...]

- * IDENTIFIER

\useexternaldocument [...¹] [...²] [...³]

- 1 IDENTIFIER
- 2 file
- 3 TEXT

\useexternalfigure [...¹] [...²] [...³] [...,⁴...]
OPTIONAL OPTIONAL OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 FILE
- 3 IDENTIFIER
- 4 *inherits from \setupexternalfigures*

\useexternalfile [...¹] [...²] [...³] [...,⁴...]

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 FILE
- 4 bodyfont =

\useexternalfiles [...¹] [...,²...]

- 1 IDENTIFIER
- 2 bodyfont =
file = FILE

\useexternalsoundtrack [...¹] [...²]

- 1 IDENTIFIER
- 2 FILE

\usemodule [...,*...]

- * IDENTIFIER

\userreferences [...*,...]

* FILE

\usespecials [...*,...]

* reset IDENTIFIER

\usesymbols [...]

* IDENTIFIER

\useURL [.¹.] [.².] [.³.] [.⁴.]

1 IDENTIFIER

2 TEXT

3 file

4 TEXT

\version [...]

* final concept temporary

\v1 [...]

* NUMBER

\WEEKDAY {...}

* TEXT

\weekday {...}

* TEXT

\whitespace

\WORD {...}

* WORD

\Word {...}

* WORD

\wordright {...}

* TEXT

\Words {... *} ... }

* WORD

\WORDS {... *} ... }

* WORD

\writebetweenlist [...¹] {...²}

1 SECTION IDENTIFIER

2 TEXT

\writetolist [...¹] {...²} {...³}

1 SECTION IDENTIFIER

2 TEXT

3 TEXT

\writetoreferencelist [...¹] {...²} {...³}

1 IDENTIFIER

2 TEXT

3 TEXT

\writetoregister [...¹] [...²] {...+³+...}
OPTIONAL

1 SINGULAR NAME

2 TEXT

3 ENTRY

The background is an abstract composition of various geometric shapes, primarily rectangles and trapezoids, in shades of light green, dark green, and grey. These shapes are layered and overlap, creating a sense of depth and movement. The overall style is modern and minimalist.

PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com